

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 18.10.2016



Version number 16

Revision: 18.10.2016

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

- **1.1 Product identifier**
- **Trade name: ASODUR-V-2370 (A-Komp.)(INDUFLOOR-IB 2370 (A-Komp.))**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the mixture** Epoxy coating
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
SCHOMBURG GmbH & Co. KG  
Aquafinstr. 2-8  
D-32760 Detmold  
Germany  
-----  
Tel: ++49 (0)5231/953-00  
Fax: ++49 (0)5231/953-123  
email: info@schomburg.de  
web: www.schomburg.de
- **Informing department:**  
Product Safety Department  
  
Tel: ++49 (0)5231/953-193  
Fax: ++49 (0)5231/953-106  
email: guido.herfort@schomburg.de

**SECTION 2: Hazards identification**

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
- 
GHS09 environment  
  
 Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.
- 
GHS07  
  

Skin Irrit. 2	H315 Causes skin irritation.
Eye Irrit. 2	H319 Causes serious eye irritation.
Skin Sens. 1	H317 May cause an allergic skin reaction.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms** GHS07, GHS09
- **Signal word** Warning
- **Hazard-determining components of labelling:**  
reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight  $\leq$  700)  
phenol  
bisphenol-F-epoxy resin  
oxirane, mono[(C12-14-alkyloxy)methyl] derivs
- **Hazard statements**  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H317 May cause an allergic skin reaction.  
H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 2)

**Trade name: ASODUR-V-2370 (A-Komp.)(INDUFLOOR-IB 2370 (A-Komp.))**

(Contd. of page 1)

• **Precautionary statements**

- P273 Avoid release to the environment.  
 P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection.  
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

• **Additional information:**

Contains epoxy constituents. May produce an allergic reaction.

• **2.3 Other hazards**

• **Results of PBT and vPvB assessment**

















- **PBT:** Not applicable.  
 • **vPvB:** Not applicable.

**SECTION 3: Composition/information on ingredients**

• **3.2 Chemical characterisation: Mixtures**

• **Description:** Preparation based on Bisphenol-A-Epichlorhydrin resin molecular weight  $\leq 700$ .

• **Dangerous components:**

CAS: 25068-38-6 NLP: 500-033-5	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight $\leq 700$ )  Aquatic Chronic 2, H411;  Skin Irrit. 2, H315;  Eye Irrit. 2, H319;  Skin Sens. 1, H317	10-25%
CAS: 38640-62-9	Diisopropylnaphtalene  Asp. Tox. 1, H304;  Aquatic Chronic 4, H413	10-25%
CAS: 61788-44-1	phenol  Aquatic Chronic 2, H411;  Skin Irrit. 2, H315;  Skin Sens. 1, H317	2.5-10%
CAS: 9003-36-5 NLP: 500-006-8	bisphenol-F-epoxy resin  Aquatic Chronic 2, H411;  Skin Irrit. 2, H315;  Eye Irrit. 2, H319;  Skin Sens. 1, H317	2.5-10%
CAS: 68609-97-2 EINECS: 271-846-8	oxirane, mono[(C12-14-alkyloxy)methyl] derivs  Skin Irrit. 2, H315;  Skin Sens. 1, H317	2.5-10%
CAS: 108-32-7 EINECS: 203-572-1	propylene carbonate  Eye Irrit. 2, H319	2.5-10%

• **Additional information** For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures**

• **4.1 Description of first aid measures**

• **General information**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Personal protection for the First Aider.

It is possible to choke in case of vomiting in unconsciousness.

Bring unconscious persons into a stable position on side.

Keep the respiratory tract free (remove dentures and vomiting).

Check the pulse. In case of heart failure you have to make a cardiac massage. In case of stoppage of breathing: artificial respiration.

Take up a doctor immediately!

• **After inhalation**

Supply fresh air or oxygen; call for doctor.

(Contd. on page 3)

**Trade name: ASODUR-V-2370 (A-Komp.)(INDUFLOOR-IB 2370 (A-Komp.))**

(Contd. of page 2)

- In case of unconsciousness bring patient into stable side position for transport.
- **After skin contact**  
Don't use solvents to clean the skin.  
Instantly wash with water and soap and rinse thoroughly.  
Change immediately contaminated clothes.
- **After eye contact**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.
- **After swallowing**  
Drink copious amounts of water and provide fresh air. Instantly call for doctor.  
Show the pack or the label to the doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents**  
CO<sub>2</sub>, extinguishing powder or water jet. Fight larger fires with water jet.
- **For safety reasons unsuitable extinguishing agents** Water with a full water jet.
- **5.2 Special hazards arising from the substance or mixture**  
Formation of poisonous gases during heating or in fires.  
In case of strong heat burst- and explosion hazard, the pressure in the container will increase. In case of fire chill the container with water-spray.
- **5.3 Advice for firefighters**
- **Protective equipment:** Wear self-contained breathing apparatus.
- **Additional information**  
Collect contaminated fire fighting water separately. It must not enter drains.  
Follow the emergency-plan.  
Burst- and explosion-danger by increaseing pressure.  
In case of fire chill the container with water spray.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Bring persons out of danger.  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow product to reach sewage system or water bodies.
- **6.3 Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling  
See Section 8 for information on personal protection equipment.  
See Section 13 for information on disposal.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
No special precautions necessary if used correctly.  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.  
Keep away from children.
- **Information about protection against explosions and fires:** No special measures required.

(Contd. on page 4)

**Trade name: ASODUR-V-2370 (A-Komp.)(INDUFLOOR-IB 2370 (A-Komp.))**

(Contd. of page 3)

- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** No special requirements.
- **Information about storage in one common storage facility:**  
Please follow the rules of the VCI-Storage-Concept for chemicals.
- **Further information about storage conditions:** Keep container tightly sealed.
- **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical systems:**  
It must be possible to wash the skin in the working area.  
Eye-wash bottle must be available.
- **8.1 Control parameters**
- **Components with critical values that require monitoring at the workplace:**  
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** The lists that were valid during the compilation were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment**
- **General protective and hygienic measures**  
The usual precautionary measures should be adhered to in handling the chemicals.  
Instantly remove any soiled and impregnated garments.  
Avoid contact with the eyes and skin.  
Be sure to clean skin thoroughly after work and before breaks.
- **Breathing equipment:** Not required.
- **Protection of hands:** Hand Protection: Nitril-rubber-latex-gloves.
- **Material of gloves**  
Butyl rubber II R: Thickness  $\geq 0,5\text{mm}$ ; Break through time  $\geq 480$  min
- **Penetration time of glove material**  
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:** Safety glasses
- **Body protection:** Protective work clothing.

### SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**

<b>Form:</b>	Liquid
<b>Colour:</b>	According to product specification
<b>Smell:</b>	Light
- **Change in condition**

<b>Melting point/Melting range:</b>	Not determined
<b>Boiling point/Boiling range:</b>	Not determined
- **Flash point:** 93 °C
- **Self-inflammability:** Product is not selfigniting.
- **Danger of explosion:** Product is not explosive.
- **Critical values for explosion:**

<b>Lower:</b>	Not determined.
---------------	-----------------

(Contd. on page 5)

**Trade name: ASODUR-V-2370 (A-Komp.)(INDUFLOOR-IB 2370 (A-Komp.))**

(Contd. of page 4)

<b>Upper:</b>	Not determined.
· <b>Steam pressure:</b>	Not determined. 0.003 hPas (20°)
· <b>Density at 20 °C</b>	1.42 g/cm <sup>3</sup>
· <b>Solubility in / Miscibility with Water:</b>	Not miscible or difficult to mix
· <b>Viscosity:</b>	
<b>dynamic at 20 °C:</b>	6300 mPas
<b>kinematic:</b>	Not determined.
· <b>9.2 Other information</b>	No further relevant information available.

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Reacts with strong acids and oxidizing agents
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
  - **Acute toxicity** Based on available data, the classification criteria are not met.
  - **LD/LC50 values that are relevant for classification:**
- 
- 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)**
- Oral LD50 >5000 mg/kg (rats)  
Dermal LD50 >2000 mg/kg (rats)
- 38640-62-9 Diisopropylnaphtalene**
- Oral LD50 >3900 mg/kg (rats)  
Dermal LD50 >4500 mg/kg (rats)
- 61788-44-1 phenol**
- Oral LD50 > 2000 mg/kg (rats)  
Dermal LD50 > 2000 mg/kg (rats)
- 9003-36-5 bisphenol-F-epoxy resin**
- Oral LD50 >10000 mg/kg (rats)  
Dermal LD50 >2000 mg/kg (rats)
- 68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs**
- Oral LD50 34600 mg/kg (rats)  
Dermal LD50 >23800 mg/kg (rabbit)
- **Primary irritant effect:**
  - **Skin corrosion/irritation**  
Causes skin irritation.
  - **Serious eye damage/irritation**  
Causes serious eye irritation.

(Contd. on page 6)

**Trade name: ASODUR-V-2370 (A-Komp.)(INDUFLOOR-IB 2370 (A-Komp.))**

(Contd. of page 5)

- **Respiratory or skin sensitisation**  
May cause an allergic skin reaction.
- **Additional toxicological information:** Sensitizing
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:**
- 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight  $\leq$  700)**
- LC50 (96h) 2 mg/l (rainbow trout)
- EC50 (48h) 1.7 mg/l (Daphnia sp.)
- EC50 (48h) 1.7 mg/l (Daphnia magna)
- NOEC 0.3 mg/l (Daphnia magna)
- 61788-44-1 phenol**
- LC50/96h 14.8 mg/l (fish toxicity)
- ERC50 3.14 mg/l (algae toxicity)
- 9003-36-5 bisphenol-F-epoxy resin**
- LC50/96h 2.54 mg/l (Leuciscus idus)
- EC50 2.55 mg/l (Daphnia magna)
- ERC50 1.8 mg/l (algae toxicity)
- 68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs**
- EC50 (48h) 1-10 mg/l (Daphnia magna)
- EC50 1-10 mg/l (Daphnia magna)
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (Self-assessment): hazardous for water.  
Do not allow product to reach ground water, water bodies or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

## SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 7)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 18.10.2016

Version number 16

Revision: 18.10.2016

Trade name: **ASODUR-V-2370 (A-Komp.)(INDUFLOOR-IB 2370 (A-Komp.))**

(Contd. of page 6)

- **European waste catalogue**

07 00 00 WASTES FROM ORGANIC CHEMICAL PROCESSES

07 02 00 wastes from the MFSU of plastics, synthetic rubber and man-made fibres

07 02 99 wastes not otherwise specified

- **Uncleaned packagings:**

- **Recommendation:** Disposal must be made according to official regulations.

**SECTION 14: Transport information**

- **14.1 UN-Number**

- **ADR, IMDG, IATA**

UN3082

- **14.2 UN proper shipping name**

- **ADR**

3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol A-(epichlorhydrin); epoxy resin(number average molecular weight&lt;700))

- **IMDG**

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol A-(epichlorhydrin); epoxy resin(number average molecular weight&lt;700)), MARINE POLLUTANT

- **IATA**

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol A-(epichlorhydrin); epoxy resin(number average molecular weight&lt;700))

- **14.3 Transport hazard class(es)**

- **ADR, IMDG, IATA**



- **Class**

9 Miscellaneous dangerous substances and articles.

- **Label**

9

- **14.4 Packing group**

- **ADR, IMDG, IATA**

III

- **14.5 Environmental hazards:**

- **Marine pollutant:**

Yes

Symbol (fish and tree)

- **Special marking (ADR):**

Symbol (fish and tree)

- **Special marking (IATA):**

Symbol (fish and tree)

- **14.6 Special precautions for user**

Warning: Miscellaneous dangerous substances and articles.

- **Kemler Number:**

90

- **EMS Number:**

F-A,S-F

- **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

- **Transport/Additional information:**

- **ADR**

- **Limited quantities (LQ)**

5L

- **Transport category**

3

(Contd. on page 8)



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 18.10.2016

Version number 16

Revision: 18.10.2016

**Trade name: ASODUR-V-2370 (A-Komp.)(INDUFLOOR-IB 2370 (A-Komp.))**

(Contd. of page 7)

· <b>Tunnel restriction code</b>	E
· <b>UN "Model Regulation":</b>	UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol A-(epichlorhydrin); epoxy resin(number average molecular weight<700)), 9, III

**SECTION 15: Regulatory information**

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **National regulations**
- **Water hazard class:**  
Water hazard class 2 (Self-assessment): hazardous for water.  
The classification based on german instructions.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**SECTION 16: Other information**

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H411 Toxic to aquatic life with long lasting effects.  
H413 May cause long lasting harmful effects to aquatic life.
- **Department issuing data specification sheet:** Environment protection department.
- **Contact:** Mr. Guido Herfort
- **Abbreviations and acronyms:**  
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
Skin Irrit. 2: Skin corrosion/irritation – Category 2  
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
Skin Sens. 1: Skin sensitisation – Category 1  
Asp. Tox. 1: Aspiration hazard – Category 1  
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2  
Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4
- **\* Data compared to the previous version altered.**

GB