


Essential for safety, the HERMÈS optoelectronic hood protects the welder's face and eyes from UV, infrared and splashes. Fully automatic, the mask switches from clear to tinted state in a fraction of a second as soon as it is primed. Comes with a headband, it frees the hands of the welder and offers all the necessary comfort for welding work.

CHARACTERISTICS


- Shade 4 / 9-13
- UV/ IR DIN 15 Protection
- Reflective paint
- External adjustment : shade or grinding
- Internal adjustment : sensitivity, delay and shade tester.

TECHNICAL DATA


Protection UV/IR	DIN 15
Classification	1/1/1/2
Clear shade	4
Dark shade	9 >13
Reaction speed	0,30 ms
Back to clear speed	0,10 > 1 sec
Field of vision	98 x 43 mm
Power supply	solar + 2 batteries (CR 2032)
Weight	520 g
Settings	Sensitivity, delay, shade, grinding
Light sensor	2
Applications	MMA 5 ▶ 400 / TIG 5 ▶ 300 / MIG-MAG 5 ▶ 400
Standards	CE / EN 175F / EN 166 / EN 379



Delivered with a headband



Sensitivity



Delay



Shade

Grinding

OPTIONS

Carry bag for helmet welding
043299




Antiperspirant headband

043466
x2



Lenses



115x 102 (x5)	103.6 x 54 (x5)
040793	040809