

LCD SPACEVIEW 5-9/9-13

Toolit®

REF.040717

Essential for safety, the SPACEVIEW optoelectronic hood protects the welder's face and eyes from UV, infrared and splashes. Fully automatic, the mask switches from clear to tinted state in a fraction of a second as soon as it is primed. Comes with a headband, it frees the welder's hands and offers all the necessary comfort for welding work.


CHARACTERISTICS

- XXL Screen
- 4 Light sensors for high sensitivity
- TIG welding > 2A
- External adjustment : shade or grinding
- Internal adjustment : sensitivity, delay
- Shade : 5-9 / 9-13
- 5-9 Shade range : for low intensity




TECHNICAL DATA

Protection UV/IR	DIN 15
Classification	1/1/1/2
Clear shade	4
Dark shade	5>9 / 9>13
Reaction time	0,10 ms
Time to return to clear state	0,15 à 0,8 sec
Field vision	100 x 93 mm
Power supply	solar + battery (CR2450)
Weight	540 g
Settings	Sensitivity, delay, shade, grind lock
Light sensor	4
Applications	MMA 5>400 / TIG 2>300 / MIG-MAG 5>400
Standards	CE / EN 175F / EN 166 / EN 379



Sensitivity



Delay



Shade


OPTIONS

Carry bag for helmet welding
043299




Antiperspirant - headband

043466
x2



LENSES



114 x 133 (x10)	043893
104 x 96 (x5)	043596