

TRACKIPRO

The long - endurance industrial asset tracker

- | | |
|--|---|
| <ul style="list-style-type: none">Extremely long battery life (up to two years, featuring advanced standby mode) | <ul style="list-style-type: none">Immediate location change alerts, Multiple geofence setup |
| <ul style="list-style-type: none">Asset tracking platform, Worldwide coverage | <ul style="list-style-type: none">Optional sensors (light, temperature) |



Example use cases

Cargo Monitoring

Location - Japan


Used to reduce theft and loss of supply chain assets and efficiently trace them 24/7.



Biotoilets Lease

Location - Europe

Used to automate visibility of the asset location and prevent ongoing theft cases.



Specifications

Trackipro

Stock Code	TRKM004 (2G) / TRKM010 (3G)
GSM Platform	MTK6250A (2G) / MTK6276 (3G)
GPS Platform	MTK3336 (2G) / MTK3337 (3G)
Bands	Quad GSM 850/ GSM900/ DCS1800/ PCS1900 (2G) GSM 850/ GSM900/ DCS1800/ PCS1900 / WCDMA 850/900/1900/2100 (3G)
GSM Antenna	Built-in Antenna
Platform Bluetooth	TI CC2541 BT4.0
Dimentions	90 mm x 64 mm x 34 mm (LxWxH)
Weight	300 gr
Active Battery Life	48 - 72 hours
Battery Type	Rechargeable Li-ion 10 000mAh
Waterproof	IP67
Functioning temperatures	-20 + 60 °C
USB Charger	USB Type-C charger
Microfone	Yes
Accelerometr	Monitor Detector
Wi - Fi	Yes



Tracking features

Trackipro

Full Data or Alert Only	Full Data
Maps	✓
Real Time Updates	✓
Geo Speed Alerts	✓
Geo Fence Alerts	✓
Travel History Available	Up to 365 days
Alerts	Email, SMS, iOS Push
Nº of Location Samples	Unlimited
Customizable tracking	✓
Global Tracking	✓
SOS Alarm	✓
Minimal update Interval	1 minute

Network & Data Transfer

Trackipro

GPRS	Yes
Data load	Full Tracking mode 35 bytes per minute
USSD load	Full Tracking mode 32 bytes per minute

Other Functions

Trackipro

Roaming Data	Yes
USSD Support	Yes

Bluetooth Specifications

Trackipro

Bluetooth CC2541	BLE V4.0
------------------	----------



GPS Specifications

Trackipro

Power Consumption	Acquisition 24 mv Track 17 mv
GPS Antenna	Ceramic antenna
Channels	22 tracking, 66 acquisition
Accuracy	< 5 meters open sky
Acquisition mode	Hot start < 2 sec, Cold start < 24 sec
Data Encryption	Available
Battery Capacity	20 to 60 days depends on mode of operation
Cached Memory	On board capacity for 1000 tracking points
Service Storage	Unlimited tracking points capacity