



Make our home energy self-sufficient.

Who we are



- ① Manufacturing bases over 200,000sqm
- ② Involving in solar industry over 10 years
- ③ Local service offices in 20 countries & regions
- ④ Local distributors in over 50 countries & regions
- ⑤ Shipment of MLPE products over 200MW per year



Why Huayu string inverter



Safer

Protection for lightning, islanding, reverse polarity, over current/voltage, AC short-circuit; Compliant with NEC2014&2017 for rapid shutdown



Smarter

Easy for parameter setting & firmware updates remotely;
Export output control within 0.5s response speed & detection accuracy within 20W; Built-in self-test program



More Flexible

Complete solutions for residential, commercial & industrial applications with multiple choices of inverter range from 1kW to 80kW



More Powerful

Maximum efficiency up to 98.9%;
4 MPPTs make the best yield of solar module arrays;
Advanced MPPT algorithm to ensure faster response to light changes



More Reliable

Wide output voltage range(Max.277/460Vac)for unstable grid;
Film capacitor with 200,000+ hours lifetime to ensure 25-year lifespan of inverter

Residential Solution

Single Phase

1kW·2kW·3kW·3.6kW·5kW·6kW



5-10
Year
Product
Warranty

50+
Country
Global
Application

97.5%
Max.
Efficiency

Protection	
DC Reverse-Polarity Protection	Yes
AC Short Circuit Protection	Yes
AC Output Overcurrent Protection	Yes
Output Overvoltage Protection	Yes
Insulation Resistance Protection	Yes
Ground Fault Monitoring	Yes
Surge Protection	Yes
Islanding Protection	Yes
Temperature Protection	Yes
Integrated DC Switch	Optional

Input Data	HYS-1K	HYS-2K	HYS-3K	HYS-3.6K	HYS-5K	HYS-6K
Max.DC Power(kW)	1.3	2.6	3.6	4.68	6.5	6.6
Max.DC Input Voltage (V)	500					
Start-up DC Input Voltage(V)	80	120	120	120	120	120
MPPT Operating Range(V)	70~500	100~500	100~500	100~500	100~500	100~500
Max.DC Input Current(A)	10	10	10	10+10	10+10	10+10
No.of MPPT/Strings per MPPT	1/1	1/1	1/1	2/1	2/1	2/1

Output Data						
Rated Output Power(kW)	1	2	3	3.6	5	6
Max. Active Power(kW)	1.1	2.2	3.3	4	5.5	6.6
Rated AC Grid Voltage(V)	230					
AC Grid Voltage Range(V)	160~300	160~300	160~300	180~300	180~300	180~300
Rated Grid Frequency(Hz)	50/60(Optional)					
Operating Phase	Single phase					
Rated AC Grid Output Current(A)	4.3	8.7	13.1	16	22	26
Max.AC Output Current(A)	4.7	9.6	14	18	24	29
Output Power Factor	>0.99					
Grid Current THD	<3%					
DC Injection Current(mA)	<0.5%					
Grid Frequency Range	47~52 or 57~62(Optional)					

Efficiency						
Max.Efficiency	97.3%	97.3%	97.5%	97.3%	97.5%	97.5%
Euro Efficiency	97.1%	97.1%	97.3%	97.1%	97.3%	97.3%
MPPT Efficiency	>99%					

Features						
DC Connection	MC-4 mateable					
AC Connection	IP65 rated plug					
Display	LCD1602					
Interface	RS485/RS232					

General Data								
Topology	Transformerless	Size(mm)	330W×347.5H×127D/127D/127D/179D/179D/179D					
Internal Consumption	<1W(Night)	Weight(kg)	7	7	7	12.5	12.5	12.5
Running Temperature	-25~60℃	Designed Lifetime	>20 years					
Ingress Protection	IP65	Grid Connection Standard	EN50438,IEC61727,VDE4105,NB/T32004(CQC),IEC62109-1-2					
Noise Emission(Typical)	<30 dB	Operating Surroundings Humidity	0-100%					
Cooling Concept	Intelligent cooling	Stafty EMC /Standard	IEC62109-1/-2,EN61000-6-1,EN61000-6-3					
Max. Operating Altitude Without Derating	2000m							

EMC/Safety/On-grid certification available for
North America · South America · Brazil · Europe · Australia · India · Korea · Israel & Thailand etc.

5kW·6kW·7kW·8kW·10kW



5-10
Year
Product
Warranty

50+
Country
Global
Application

98.3%
Max.
Efficiency

Protection

DC Reverse-Polarity Protection	Yes
AC Short Circuit Protection	Yes
AC Output Overcurrent Protection	Yes
Output Overvoltage Protection	Yes
Insulation Resistance Protection	Yes
Ground Fault Monitoring	Yes
Surge Protection	Yes
Islanding Protection	Yes
Temperature Protection	Yes
Integrated DC Switch	Optional

Input Data

	HYS-5K-3	HYS-6K-3	HYS-7K-3	HYS-8K-3	HYS-10K-3
Max.DC Power(kW)	6.5	7.8	9.1	10.4	12
Max.DC Input Voltage (V)	900				
Start-up DC Input Voltage(V)	250				
MPPT Operating Range(V)	200~800				
Max.DC Input Current(A)	10+10				
No.of MPPT/Strings per MPPT	2/1				

Output Data

Rated Output Power(kW)	5	6	7	8	10
Max. Active Power(kW)	5.5	6.6	7.7	8.8	11
Rated AC Grid Voltage(V)	380/400				
AC Grid Voltage Range(V)	277~460				
Rated Grid Frequency(Hz)	50/60(Optional)				
Operating Phase	Three phase				
Rated AC Grid Output Current(A)	7.2	8.7	10.1	11.6	14.5
Max.AC Output Current(A)	8	9.57	11.11	12.76	16
Output Power Factor	>0.99				
Grid Current THD	<3%				
DC Injection Current(mA)	<0.5%				
Grid Frequency Range	47~52 or 57~62(Optional)				

Efficiency

Max.Efficiency	98.3%
Euro Efficiency	97.5%
MPPT Efficiency	>99%

Features

DC Connection	MC-4 mateable
AC Connection	IP65 rated plug
Display	LCD1602
Interface	RS485/RS232

General Data

Size(mm)	385W×479H×184D	Cooling Concept	Intelligent cooling
Weight(kg)	15	Max. Operating Altitude Without Derating	2000m
Topology	Transformerless	Designed Lifetime	>20 years
Internal Consumption	<1W(Night)	Grid Connection Standard	EN50438 , IEC61727 , VDE4105 , NB/T32004(CQC) , IEC62109-1-2
Running Temperature	-25~60℃	Operating Surroundings Humidity	0-100%
Ingress Protection	IP65	Stafty EMC /Standard	IEC62109-1/-2 , EN61000-6-1 , EN61000-6-3
Noise Emission(Typical)	<30 dB		

EMC/Safety/On-grid certification available for
North America · South America · Brazil · Europe · Australia · India · Korea · Israel & Thailand etc.

12kW·15kW·20kW·25kW



5
Year
Product
Warranty

50+
Country
Global
Application

98.6%
Max.
Efficiency

Protection	
DC Reverse-Polarity Protection	Yes
AC Short Circuit Protection	Yes
AC Output Overcurrent Protection	Yes
Output Overvoltage Protection	Yes
Insulation Resistance Protection	Yes
Ground Fault Monitoring	Yes
Surge Protection	Yes
Islanding Protection	Yes
Temperature Protection	Yes
Integrated DC Switch	Optional

Input Data	HYS-12K-3	HYS-15K-3	HYS-20K-3	HYS-25K-3
Max.DC Power(kW)	15.6	18	24	32.5
Max.DC Input Voltage (V)	1000			
Start-up DC Input Voltage(V)	250			
MPPT Operating Range(V)	200~800			
Max.DC Input Current(A)	20+20	20+20	20+20	30+30
No.of MPPT/Strings per MPPT	2/2	2/2	2/2	2/3

Output Data				
Rated Output Power(kW)	12	15	20	25
Max. Active Power(kW)	13.2	16.5	22	27.5
Rated AC Grid Voltage(V)	380/400			
AC Grid Voltage Range(V)	277~460			
Rated Grid Frequency(Hz)	50/60(Optional)			
Operating Phase	Three phase			
Rated AC Grid Output Current(A)	17.4	21.8	29	36.2
Max.AC Output Current(A)	19.14	24	31.9	39.9
Output Power Factor	>0.99			
Grid Current THD	<3%			
DC Injection Current(mA)	<0.5%			
Grid Frequency Range	47~52 or 57~62(Optional)			

Efficiency	
Max.Efficiency	98.6%
Euro Efficiency	97.8%
MPPT Efficiency	>99%

Features	
DC Connection	MC-4 mateable
AC Connection	IP65 rated plug
Display	LCD1602/LCD240X160
Interface	RS485/RS232

General Data			
Size(mm)	455W×573H×265D	Cooling Concept	Intelligent cooling
Weight(kg)	30.5	Max. Operating Altitude Without Derating	2000m
Topology	Transformerless	Designed Lifetime	>20 years
Internal Consumption	<1W(Night)	Grid Connection Standard	EN50438 , IEC61727 , VDE4105 , NB/T32004(CQC) , IEC62109-1-2
Running Temperature	-25~60℃	Operating Surroundings Humidity	0-100%
Ingress Protection	IP65	Stafty EMC /Standard	IEC62109-1/-2 , EN61000-6-1 , EN61000-6-3
Noise Emission(Typical)	<30 dB		

EMC/Safety/On-grid certification available for
North America · South America · Brazil · Europe · Australia · India · Korea · Israel & Thailand etc.

30kW·33kW·35kW·40kW·50kW



5
Year
Product
Warranty

50+
Country
Global
Application

98.7%
Max.
Efficiency

Protection	
DC Reverse-Polarity Protection	Yes
AC Short Circuit Protection	Yes
AC Output Overcurrent Protection	Yes
Output Overvoltage Protection	Yes
Insulation Resistance Protection	Yes
Ground Fault Monitoring	Yes
Surge Protection	Yes
Islanding Protection	Yes
Temperature Protection	Yes
Integrated DC Switch	Optional

Input Data	HYS-30K-3	HYS-33K-3	HYS-35K-3	HYS-40K-3	HYS-50K-3
Max.DC Power(kW)	36	36	39.6	52	65
Max.DC Input Voltage (V)	1000				
Start-up DC Input Voltage(V)	250				
MPPT Operating Range(V)	200~850				
Max.DC Input Current(A)	30+30	30+30	30+30	30+30+30	30+30+30+30
No.of MPPT/Strings per MPPT	2/3	2/3	2/3	3/3	4/3

Output Data					
Rated Output Power(kW)	30	33	35	40	50
Max. Active Power(kW)	33	36.3	38.5	44	55
Rated AC Grid Voltage(V)	380/400				
AC Grid Voltage Range(V)	277~460				
Rated Grid Frequency(Hz)	50/60(Optional)				
Operating Phase	Three phase				
Rated AC Grid Output Current(A)	43.5	48	50.7	58	72.4
Max.AC Output Current(A)	47.85	52.8	55.8	63.8	79.64
Output Power Factor	>0.99				
Grid Current THD	<3%				
DC Injection Current(mA)	<0.5%				
Grid Frequency Range	47~52 or 57~62(Optional)				

Efficiency	
Max.Efficiency	98.7%
Euro Efficiency	98.3%
MPPT Efficiency	>99%

Features	
DC Connection	MC-4 mateable
AC Connection	IP65 rated plug
Display	LCD240X160
Interface	RS485/RS232

General Data			
Size(mm)	700W×684H×307D	Cooling Concept	Intelligent cooling
Weight(kg)	55	Max. Operating Altitude Without Derating	2000m
Topology	Transformerless	Designed Lifetime	>20 years
Internal Consumption	<1W(Night)	Grid Connection Standard	EN50438 , IEC61727 , VDE4105 , NB/T32004(CQC) , IEC62109-1-2
Running Temperature	-25~60℃	Operating Surroundings Humidity	0-100%
Ingress Protection	IP65	Stafty EMC /Standard	IEC62109-1/-2 , AS3100 , EN61000-6-1
Noise Emission(Typical)	<30 dB		

EMC/Safety/On-grid certification available for
North America · South America · Brazil · Europe · Australia · India · Korea · Israel & Thailand etc.

60kW·70kW·75kW·80kW



5

Year
Product
Warranty

50+

Country
Global
Application

98.9%

Max.
Efficiency

Protection	
DC Reverse-Polarity Protection	Yes
AC Short Circuit Protection	Yes
AC Output Overcurrent Protection	Yes
Output Overvoltage Protection	Yes
Insulation Resistance Protection	Yes
Ground Fault Monitoring	Yes
Surge Protection	Yes
Islanding Protection	Yes
Temperature Protection	Yes
Integrated DC Switch	Optional

Input Data	HYS-60K-3	HYS-70K-3	HYS-75K-3	HYS-80K-3
Max.DC Power(kW)	78	91	97.5	96
Max.DC Input Voltage (V)	1000			
Start-up DC Input Voltage(V)	250			
MPPT Operating Range(V)	200~850			
Max.DC Input Current(A)	30+30+30+30	40+40+40+40	40+40+40+40	40+40+40+40
No.of MPPT/Strings per MPPT	4/3	4/4	4/4	4/4

Output Data				
Rated Output Power(kW)	60	70	75	80
Max. Active Power(kW)	66	77	82.5	88
Rated AC Grid Voltage(V)	380/400			
AC Grid Voltage Range(V)	277~460			
Rated Grid Frequency(Hz)	50/60(Optional)			
Operating Phase	Three phase			
Rated AC Grid Output Current(A)	87.8	101.5	108.7	115.9
Max.AC Output Current(A)	95.7	111.6	119.6	127.5
Output Power Factor	>0.99			
Grid Current THD	<3%			
DC Injection Current(mA)	<0.5%			
Grid Frequency Range	47~52 or 57~62(Optional)			

Efficiency	
Max.Efficiency	98.9%
Euro Efficiency	98.3%
MPPT Efficiency	>99%

Features	
DC Connection	MC-4 mateable
AC Connection	IP65 rated plug
Display	LCD240X160
Interface	RS485/RS232

General Data			
Size(mm)	700W×684H×307D	Cooling Concept	Intelligent cooling
Weight(kg)	60	Max. Operating Altitude Without Derating	2000m
Topology	Transformerless	Designed Lifetime	>20 years
Internal Consumption	<1W(Night)	Grid Connection Standard	EN50438 , IEC61727 , VDE4105 , NB/T32004(CQC) , IEC62109-1-2
Running Temperature	-25~60℃	Operating Surroundings Humidity	0-100%
Ingress Protection	IP65	Stafty EMC /Standard	IEC62109-1/-2 , AS3100 , EN61000-6-1
Noise Emission(Typical)	<30 dB		

EMC/Safety/On-grid certification available for
North America · South America · Brazil · Europe · Australia · India · Korea · Israel & Thailand etc.

Make our home energy self-sufficient.



Huayu Global Offices (Sales & Technical Support)

Huayu North America

Huayu USA

E-mail: info@huayu-energy.com
sales1@huayu-energy.com
Add: 20 Fairbanks, Irvine, CA 92618

Huayu FL

Tel: +1(786)970-3940
E-mail: info@huayu-energy.com
Add: 2900 NW 112 Ave, Doral, FL 33172

Huayu CA

Tel: +1(559)909-8202
E-mail: info@huayu-energy.com
Add: 8200 W Doe Ave, Visalia, CA 93291

Huayu NM

Tel: +1(505)980-1437
E-mail: info@huayu-energy.com
Add: 2139 Don Andres PL SW,
Albuquerque, NM 87105

Huayu WA

Tel: +1(509)531-4107
E-mail: info@huayu-energy.com
Add: 5100 Elm Road, Pasco, WA 99301

Huayu NY

Tel: +1(949)293-7016
E-mail: info@huayu-energy.com
Add: 555 Tenth Ave 17A, New York, NY 10018

Huayu APAC

Tel: +84-2513877580
E-mail: info@huayu-energy.com
sales2@huayu-energy.com
Add: 151, Khong Tu, Xuan Trung Ward,
Long Khanh City, Dong Nai Province,
Vietnam

Huayu LATAM

Tel: +52-13339541349
E-mail: info@huayu-energy.com
Add: Calzada San Juan No. 1570,
Col. Ciudad Granja C.P. 45010,
Zapopan, Jalisco, México

Huayu Benelux & EMEA

Tel: +31-624 226 499 (Sales & Marketing)
+31-624 168 825 (Technical Support)
E-mail: sales5@huayu-energy.com
Add: Meeren Vaart 164, 1068 ZZ Amsterdam,
the Netherlands

Huayu Eastern Europe

Tel: +48-664340 224
E-mail: sales4@huayu-energy.com
Add: Krakow, Poland

Huayu Turkey

Tel: +90-5332400825
E-mail: info@huayu-energy.com
Add: Kemalpaşa Cad. no: 329 PINARBASI,
Bornova/Izmir

Huayu Australasia

Tel: +61-412898238
E-mail: info@huayu-energy.com
gricol.yang@huayu-energy.com
Add: 393 Upper Heidelberg Road, Ivanhoe,
VIC 3079 Australia

Huayu Chile & Bolivia

Tel: +56-996527136
E-mail: info@huayu-energy.com
christian@huayu-energy.com
Add: Tamarugal 4043, Iquique 1100000,
Chile

Huayu Nigeria & Western Africa

Tel: +234-8154863996
E-mail: info@huayu-energy.com
Add: 2nd floor, UAC Commercial
Complex, Plot 273 Ademolegun Street,
Central Business District, Abuja

Huayu Northern Africa

Tel: +212-673734843
E-mail: info@huayu-energy.com
said@huayu-energy.com
Add: 5 Av de la Marche, Verte Res Assafir
Bloc B, Entre Sol N° 7, 90020 TANGER,
Morocco

Huayu Israel

Tel: +972-5444 89996
E-mail: info@huayu-energy.com
Add: 2 Oren Street, Israel 4585500

Huayu Brazil

Tel: +55-319467 5735 (Technical Support)
E-mail: info@huayu-energy.com
thiago@huayu-energy.com
Add: No 7 Hum Street, Lagoa Santa City,
State of Minas Gerais 33.400-000, Brazil

Huayu New Energy Headquarters

Tel: +86-574-89258801
E-mail: info@huayu-energy.com
Add: No. 456 Xingning Road, Ningbo 315100, P.R. China

Huayu(Zhejiang)New Energy Technologies Co., Ltd.

www.huayu-energy.com