AirStorm 24" Fan



MODEL	DESCRIPTION	SHUTTER	ROUGH OPENING	RPM	DRIVE	SPEED	HP
AS-24EDDLP	24" w/o cone	PVC	34.5" x 34.5"	1075	Direct	Variable	1/3
AS-24EDDLP-V	24",w/VFD drive w/o cone	PVC	34.5" x 34.5"	1100	Direct	Variable	1/3 (3 Ph)
AS-24EDDLP-L	24",w/o VFD drive & cone	PVC	34.5" x 34.5"	1100	Direct	Variable	1/3 (3 Ph)
AS-24206	24" Poly Cone						



A 115/230V 1/3 HP motor powers the AirStorm 14", 18" and 24" fans. Stainless steel motor mounts and hardware furnish superior corrosion resistance.



Motor-matched, compsite fiberglass props outlast plastic or aluminum. Resin transfer fiberglass housings feature UV stabilizers to last in the harshest environmental conditions.



White PVC shutters feature full-length spring steel rods instead of plastic pins in the ends which lock into a heavy PVC frame with reinforced corners. True airfoil shutter vanes reduce air drag. *This shutter is included with the fan



Shown with the optional discharge cone.
Heavy-duty fan guards with baked on finish. Smooth interior and exterior are easier to wash.

AirStorm 36" Fan



MODEL	DESCRIPTION	SHUTTER	ROUGH OPENING	RPM	DRIVE	SPEED	HP
AS-36EDDLPA	36" w/o cone	Plastic	43.5" x 43.5"	850	Direct	Variable	1/2
AS-36EDDLPA3	36", 3-PH w/o cone	Plastic	43.5" x 43.5"	850	Direct	Single	1/2 (3 Ph)
AS-36EDDLP-V	36", w/VFD drive w/o cone	Plastic	43.5" x 43.5"	850	Direct	Single	1/2 (3 Ph)
AS-36EDDLP-L	36", w/o VFD drive & cone	Plastic	43.5" x 43.5"	850	Direct	Single	1/2 (3 Ph)
AS-36206	36" Poly Cone						



A high service factor 1/2 HP motor powers the AirStorm 36" fan. The high S.F. rating provides protection from motor failures caused by varying rural electrical voltage. Stainless steel motor mounts and hardware provide superior corrosion resistance.



Motor-matched, composite props outlast plastic or aluminum. Resin transfer fiberglass housings feature UV stabilizers to last in the harshest environmental conditions. Heavy-duty fan guards with baked on finish.



White PVC shutters feature full
--length spring steel rods instead of
plastic pins in the ends— which lock
into a heavy PVC frame with reinforced
corners. True airfoil shutter vanes
reduce air drag.

*This shutter is included with the fan



Shown with the optional discharge cone.

Smooth interior and exterior are easier to wash.