



Primer S

1.SPECIFICATIONS

PRIMER S is white and can be coloured if necessary, it gives a slightly "rough"-effect primer specifically employed to facilitate the adhesion of decorative finishes such as (STUCCOMARMO, DECORA'etc) particularly smooth supports with a low absorption degree (such as concrete, cellular cement, plasterboard, plaster).

2.COMPOSITION

Acrylic emulsion, special surface-active agents, quartz grains, other additives

3.METHODS OF APPLICATION

Apply directly with a paint brush or roller, dilute with 20-40% of water

4.technical data

SPECIFIC WEIGHT: 1,682 Kg./Lt. +/- 0,5%

VISCOSITY: thixotropic

COLOUR: white

YIELD: 7-8 m²/Lt.

DILUTION: 20 - 40% with water

PACKAGING: Lt, 15, Lt. 4 , Lt.0,750 polyethylene containers

DRYING: 30 minutes to the touch – completely dry in 24 hours at 20°C

OVERPAINTING DEGREE: 24h

APPLICATION: brush or roller

PRESERVATION: 36 months in the intact packages, away from temperature changes

5.ITEM OF SPECIFICATIONS

Pre-treatment of crumbly wall surfaces with one coat of highly-adherent rough primer like PRIMER S produced by Spiver Ltd.

Price inclusive of the material and implementation, except the scaffoldings per square metre: €.....

NB The above-mentioned data are susceptible of variations. Spiver Ltd. Is not responsible for any negative result depending on the application of the product out of the company's control and on the agents unrelated to the product quality.



Emotion with paint ...

SPIVER s.r.l.

contrada Babbaurra S.S. 122

93100 Caltanissetta (CL)

Tel. +39 0934 57 77 91 Fax +39 0934 58 87 95

www.spiver.it - info@spiver.it