



## Nahir



### 1. SPECIFICATIONS AND FIELDS OF EMPLOYMENT

Flexible wall coating, it allows you to obtain decorative finishes with a thickness of extraordinary beauty with extreme ease of implementation and with a pleasant tactile softness like an "egg shell". NAHIR allows the designer to pull out all his inspiration and his endless creativity and allows for customizable working. NAHIR is used as a base (tinted white or coloured) for shaping relief of any form and in the absence of absolute withdrawal up to 5 mm. thick.

When completely dried it can be decorated with our VELATURA (properly pigmented). In the application process NAHIR enhances its characteristics:

- Excellent fluency and lightness in application.
- High "open time" (in order to reduce or cancel the problem of joints)
- Excellent power filler
- No withdrawal up to a thickness of 5 mm.

### 2. COMPOSITION

Valuable resins in water emulsion, special extenders high resistance, titanium oxides and / or iron, additives. And free from harmful substances such as solvents and pigment-based or lead chromate.

### 3. METHOD OF APPLICATION:

NAHIR is proposed with three decorative techniques of great aesthetic impact: NAHIR RIGATO, NAHIR BROCCATO, NAHIR CRACKLE'.

#### NAHIR RIGATO

This is an innovative solution furnishing of extraordinary beauty and ease of implementation that is suitable for use in both style ethnic (wengè effect or effect douglas), in a modern style (dark shades and stripes dyed light).

#### Smooth walls well cohesive or plasterboard

Apply one coat of PRIMER S with roller or brush, minimum 12 hours after proceed with the drafting of NAHIR with a plastic trowel taking care to distribute a uniform layer of between 2 to 3 mm. Immediately after with PETTINARTE tool finish NAHIR in a vertical or horizontal (depending on the desired effect); after drying (after at least 24 hours), apply VELATURA with a paint brush following the directions of the lines and remove the excess product with SPUGNARTE tool, always following the direction of the lines design.

#### NAHIR BROCCATO

It also has a solution furnishing of great impact, ease of implementation, which is used in modern environments that in old-antique style.

#### Smooth walls well cohesive or plasterboard

Apply one coat of PRIMER S with roller or brush, minimum 12 hours after proceed with the drafting of NAHIR with a plastic trowel taking care to distribute a uniform layer of between 2 to 3 mm. Immediately after with BROCCATO trowel tool finish NAHIR with movements in circular motion. After drying (after at least 24h), apply VELATURA with a

paint brush and remove immediately the excess product with TRANSPARENT TROWEL tool.

#### NAHIR CRACKLE'

This is a very prestigious finish: particular and original if finished with VELATURA CLASSIC, also elegant and valuable if further complemented with VELATURA PERLATA.

#### Smooth walls well cohesive or plasterboard

Apply one coat of PRIMER S with roller or brush, minimum 12 hours after apply a coat of FISSATIVO REOSAN without diluting. After 24 hours proceed with the application of the BASE CRACKLE with a Roller, without diluting. After 12 hours apply NAHIR with a special brush "SPLATER DECORA" taking care to distribute a uniform layer between 2 to 3mm. Within 24 hours the Nahir will give its cracked effect. After that complete the effect applying 1 or 2 coats of VELATURA CLASSIC or VELATURA PERLATA with a paint brush and finishing the effect with SPUGNARTE tool or with a glove.

It is very important that during this phase that the temperature doesn't go below 15°C.

### 4. TECHNICAL DATA

**SPECIFIC WIEGHT:** 1,083 +/- 0,5% kg./Lt..  
**FILM ASPECT:** matt.  
**COLOURS:** white + colours from our color chart.  
**VISCOSITY:** 40000 cps +/- 5%  
**YIELD:** 2 - 3 m<sup>2</sup>/Lt. per coat.  
**DILUTION:** ready to use  
**PACKAGE:** buckets of Lt. 15-5-



*Emotion with paint ...*

**SPIVER s.r.l.**

contrada Babbaurra S.S. 122  
 93100 Caltanissetta ( CL )

Tel. +39 0934 57 77 91 Fax +39 0934 58 87 95

[www.spiver.it](http://www.spiver.it) - [info@spiver.it](mailto:info@spiver.it)



## Nahir



0,750.

**DRYING:** 2 – 3 h to touch , 7 days to dry completely (temperature 20°C)

**APPLICATION:** rowel or brush.

**PRESERVATION:** 36 months in the intact packages, away from temperature changes.

**HS-CODE:** 32091000

micro granular rough type PRIMER SPIVER Srl. ,one coat of FISSATIVO REOSAN and one coat of BASE CRACKLE ', and finished VELATURA of SPIVER Srl.

The price includes the equipment and implementation, excluding the scaffolding m<sup>2</sup> €.....

### 5.ITEM OF SPECIFICATIONS

#### NAHIR RIGATO

Decoration of internal wall surfaces with shaped stripe effect on the type of RIGATO NAHIR SPIVER Srl, the consumption of about 2-3 m<sup>2</sup> / Lt. After applying a base coat of micro granular rough type PRIMER S SPIVER Srl., and finished with VELATURA of SPIVER Srl.

The price includes the equipment and implementation, excluding the scaffolding m<sup>2</sup> €.....

#### NAHIR BROCCATO

Decoration of internal wall surfaces coated mural shaped brocade effect on the type of BROCCATO NAHIR SPIVER Srl, the consumption of about 2-3 m<sup>2</sup> / Lt. After applying a base coat of micro granular rough type PRIMER S SPIVER Srl., and finished with VELATURA of SPIVER Srl.

The price includes the equipment and implementation, excluding the scaffolding m<sup>2</sup> €.....

#### NAHIR CRACKLE'

Decoration of internal wall surfaces coated mural shaped effect cracklè type NAHIR CRACKLE 'of SPIVER Srl, the consumption of about 2-3 m<sup>2</sup> / Lt. After applying a base coat of

NB: the above-mentioned data are susceptible of variations. Spiver Ltd. Is not responsible for any negative result depending on the application of the product out of the company's control and on the agents unrelated to the product quality.



*Emotion with paint ...*

**SPIVER s.r.l.**

contrada Babbaurra S.S. 122  
93100 Caltanissetta ( CL )

Tel. +39 0934 57 77 91 Fax +39 0934 58 87 95

**www.spiver.it - info@spiver.it**