



Velatura

1.SPECIFICATIONS AND FIELDS OF EMPLOYMENT

VELATURA is a semi-covering finish for both internal and external formulated with acrylic-siloxanic emulsions characterized by a fine decorative antique effect. It can be applied on both smooth and rough, mineral and synthetic supports. When applied on outdoor on our SPIVERSIL ANTICO), it produces some elegant light-and-shade effects which enriches and protect the external wall finish guaranteeing both an excellent water-repellent power and at the same time un altering the high permeability to water vapour of the surface (the VELATURA RUSTICA FINISH). When applied on indoor supports, it can be applied after a previous treatment with REOSAN OPACO (if a smooth final effect is required), so as to guarantee an good wash ability and an excellent resistance against bacteria. (The VELATURA CLASSIC FINISH). The decorative flexibility the antique effect and excellent performance of color resistance make VELETURA stand out as an excellent product for external wall finishes especially in old city centers and also for the decorating of old fashion internal environments.

2.COMPOSITION

Acrylic-siloxanic emulsion, lightproof pigments, additives.

3.METHODS OF APPLICATION

VELATURA is supplied as a neutral base of Lt. 4 which can be colored either by ARTHE CONCENTRATO or GLOBAL TINTING SYSTEM according to

the indications specified in the color chart.

THE VELATURA "RUSTICA" finish made up of SPIVERSIL ANTICO and VELATURA

For internal application on smooth surfaces (gypsum, plaster boards, or smooth paint surfaces) it is extremely necessary to apply 1 coat of PRIMER RV, after 24 hours you can directly apply SPIVERSIL ANTICO with a stainless steel float and give the finish effect with a plastic float , after 24 hours in order to obtain the VELATURA RUSTICA finish apply the VELATURA (colored chosen from the color chart) with a paint brush and obtain the finished effect either with a sponge float of a woolen glove which is used for decorating. For external surfaces such as cement or lime base or surfaces with RASSANTE W-04, the base must be solid and there shouldn't be any trace of old paint in this case it is advisable to use special products in order to remove trace of old paint etc.Then apply 1 coat of SPIVERSIL PRIMER(special fixing primer) diluted 100% . after 24 hours apply SPIVERSIL LISCIO diluted at a ratio of 50% with water wait for a least 12 hours and then apply SPIVERSILANTICO with a stainless steel float and give the finish effect with a plastic float. after 24 hours in order to obtain the VELATURA RUSTICA finish apply the VELATURA (colored chosen from the color chart) with a paint brush and obtain the finished effect either with a sponge float of a woolen glove which is used for decorating.

THE VELATURA "CLASSIC" finish made up of REOSAN

OPACO and VELATURA Sandpaper, putty and dust any imperfections with STUCCOMURO or POLISTUCK and apply 1 coat of FISSATIVO UNIVERSALE which should be correctly diluted with water at a ratio of 1:5 fino ad 1:10 depending on the absorbing of the surface. Leave to dry for at least 4 hours and then apply 2 coats of water paint REOSAN OPACO correctly diluted (please consult the Technical data sheet) leave 4 to 5 hours between each application. After 24 hours proceed with the application of VELATURA (choose a color from our color chart) with a paint brush and immediately while the paint is still fresh go over the surface with circular movements with a special woolen glove. Warning : do not apply on a damp wall or if the weather conditions are not favorable for example in foggy or raining conditions. Apply when the temperature is between 5 and 30°C.

4.TECHNICAL DATA

SPECIFIC WEIGHT: 1,040 +/- 5%

PACKAGING : buckets of Lit 4

COLOURS: colours from the colour chart

YIELD: 5-7 square meters/ lit per coat

PRESERVATION: 24 months in the intact packages, away from temperature changes

DRYING: 12 - 24 hours at a temperature of 20°C

DILUTION: ready to use.

VISCOSITY :200" - 250" Ford Cup n.4

APPLICATION: by brush.

HS-CODE: 32091000

5.ITEM OF SPECIFICATIONS



Emotion with paint ...

SPIVER s.r.l.

contrada Babbaurra S.S. 122

93100 Caltanissetta (CL)

Tel. +39 0934 57 77 91 Fax +39 0934 58 87 95

www.spiver.it - info@spiver.it



Velatura

Decorating and protection of the external and internal surfaces with acrylic silicate water repellent and resistant to water vapour, with an antique type finish of VELATURA Spiver srl applied by brush and finisher either by brush or sponge. The price includes the equipment and implementation, excluding the scaffolding sqm.
€.....

NB The above-mentioned data are susceptible of variations. Spiver Ltd. Is not responsible for any negative result depending on the application of the product out of the company's control and on the agents unrelated to the product quality



Emotion with paint ...

SPIVER s.r.l.

contrada Babbaurra S.S. 122
93100 Caltanissetta (CL)

Tel. +39 0934 57 77 91 Fax +39 0934 58 87 95

www.spiver.it - info@spiver.it