




**DISTRIBUTORI
OLEODINAMICI**

WMM25

**MANUALLY OPERATED
DIRECTIONAL CONTROL VALVES**



WMM25 SERIES MANUALLY OPERATED DIRECTIONAL CONTROL VALVES ARE DIRECT TYPE DIRECTIONAL SPOOL VALVES. THESE VALVES ARE USED TO THE START, STOP AND DIRECTION OF FLOW. THIS SERIES WITH DETENT OR RETURN SPRING ARE AVAILABLE.




TECHNICAL DATA


SIZE		25
MAX. FLOW RATE (L/MIN)		450
OPERATING PRESSURE (MPA)	A, B, P PORTS	31.5
	T PORT	25
WEIGHT (KG)		39.2
VALVE BODY (MATERIAL)		CASTING PHOSPHATING SURFACE

CHARACTERISTIC CURVES


ΔP -Q CHARACTERISTIC CURVES - SPOOL TYPE E, R, W



ΔP -Q CHARACTERISTIC CURVES - SPOOL TYPE G, T



ΔP -Q CHARACTERISTIC CURVES - SPOOL TYPE S, F, H, J, L, M, Q, U, V, W, C, D, K, Z






DISTRIBUTORI
OLEODINAMICI

WMM25


MANUALLY OPERATED
DIRECTIONAL CONTROL VALVES

SPOOL SYMBOLS

2-POSITION VALVES




3-POSITION VALVES



SEE ALSO:
WMM6, WMM10,
WMM16

SUBPLATE INSTALLATION DIMENSIONS





DISTRIBUTORI
OLEODINAMICI

WMM25

MANUALLY OPERATED
DIRECTIONAL CONTROL VALVES

ORDER CODE

		WMM	25						
--	--	-----	----	--	--	--	--	--	--

H=35MPa

3=3-WAY
4=4-WAY

25=25 SIZE

SPOOL TYPE

10=10 SERIES
50=50 SERIES

NO CODE=SPRING RETURN WITHOUT DETENT
F=DETENT WITHOUT SPRING RETURN

NO CODE=HANDLE
ON SIDE OF PORT A
L=HANDLE
ON SIDE OF PORT B

NO CODE=MINERAL SUBSTANCE
HYDRAULIC OIL
V=PHOSPHATE EATER
HYDRAULIC OIL

NO CODE=WITHOUT THROTTLE INSERT
B0.8=THROTTLE 0.8 MM
B1.0=THROTTLE 1.0 MM
B1.2=THROTTLE 1.2 MM