


RoHS Compliant Product
A suffix of "-C" specifies halogen & lead-free


FEATURES

- Built-in bias resistors enable the configuration of an inverter circuit without connecting external input resistors (see equivalent circuit).
- The bias resistors consist of thin-film resistors with complete isolation to allow positive biasing of the input. They also have the advantage of almost completely eliminating parasitic effects.
- Only the on/off conditions need to be set for operation, making device design easy.

EQUIVALENT CIRCUIT




DTC144EE (SOT-523)



Abbreviated symbol : 26

DTC144EUA (SOT-323)




Abbreviated symbol : 26

DTC144EM (SOT-723)




Abbreviated symbol : 26

DTC144ECA (SOT-23)



Abbreviated symbol : 26

DTA144ESA (TO-92S)



ABSOLUTE MAXIMUM RATINGS (T_A=25°C unless otherwise noted)


Parameter	Symbol	Limits (DTC144E□)					Unit
		M	E	UA	CA	SA	
Collector-Base Voltage	V _{CC}	50					V
Input voltage	V _{IN}	-10~40					V
Output current	I _O	30					mA
	I _{C(MAX)}	100					
Power dissipation	P _D	100	150	200		300	mW
Junction & Storage temperature	T _J , T _{STG}	150, -55~150					℃

ELECTRICAL CHARACTERISTICS ($T_A=25^\circ\text{C}$ unless otherwise noted)


Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Conditions
Input voltage	$V_{I(\text{off})}$	0.5	-	-	V	$V_{CC}=5\text{V}$, $I_O=100\mu\text{A}$
	$V_{I(\text{on})}$	-	-	3		$V_O=0.3\text{V}$, $I_O=2\text{mA}$
Output voltage	$V_{O(\text{on})}$	-	-	0.3	V	$I_O/I_I=10\text{mA}/0.5\text{mA}$
Input current	I_I	-	-	0.18	mA	$V_I=5\text{V}$
Output current	$I_{O(\text{off})}$	-	-	0.5	μA	$V_{CC}=50\text{V}$, $V_I=0$
DC current gain	G_I	68	-	-		$V_O=5\text{V}$, $I_O=5\text{mA}$
Input resistance	R_1	32.9	47	61.1	K Ω	
Resistance ratio	R_2/R_1	0.8	1	1.2		
Transition frequency	f_T	-	250	-	MHz	$V_O=10\text{V}$, $I_O=5\text{mA}$, $f=100\text{MHz}$

CHARACTERISTIC CURVES


ON Characteristics




OFF Characteristics




$V_{O(ON)}$ — I_O



G_I — I_O



C_O — V_R



P_D — T_a

