

FLOATMAX

FEATURES

- Directional Lug
- Robust Lug

BENEFITS

- Better Traction
- Self Cleaning
- Better Grip

FEATURES

- Robust Centre Blocks
- Flatter Crown Width

BENEFITS

- Low Vibration and Smooth Run on Hard Surface
- Higher Footprint Enables More Floating Characteristics



FEATURES

- Higher V/R Ratio

BENEFITS

- Better Life


FEATURES

- Rounded Shoulder

BENEFITS

- Less Soil Disturbance

MACHINERY



Trailer

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph /mph					
				SW	OD				Static	10	30	40	50	65
				mm	mm					6	19	25	31	40
				in	in					Recommend load kg /lbs				
560/60R22.5	161D	TL	AG16.00	543 21.4	1244 49	561 22.1	3810 150	1.2	5270	4120	3460	3110	2770	2290
								1.7	11610	9070	7620	6850	6100	5040
								1.6	6230	4880	4090	3690	3280	2710
								2.3	13720	10750	9010	8130	7220	5970
								2.4	7910	6190	5190	4680	4160	3440
								3.5	17420	13630	11430	10310	9160	7580
								2.8	8650	6770	5680	5110	4550	3760
								4.1	19050	14910	12510	11260	10020	8280
								3.6	10010	7830	6570	5920	5260	4350
								5.2	22050	17250	14470	13040	11590	9580
								4	10640	8330	6980	6290	5600	4625
								5.8	23440	18350	15370	13850	12330	10190

All tires confirms ETRTO T&RA & STRO standards