

TORQUEMAX



FEATURE

- Stepped lug design

BENEFIT

- Better Grip

FEATURE

- Tilted lug tip

BENEFIT

- Lower vibration at high speeds.

FEATURE

- Strong & wider lugs

BENEFIT

- Provides higher contact area leading to higher life

FEATURE

- Wider tread width

BENEFIT

- Lower Compaction

FEATURE

- Lower lug angle at the shoulder

BENEFIT

- Better traction

FEATURE


- Rounder shoulder

BENEFIT

- Lesser soil/crop damage

*Lower Compaction, Higher Traction and Better Roadability

MACHINERY



Tractor

Size	Rim	Unloaded dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. press.	maximum load, kg (lbs) Speed, km/h (mph)							
		SW	OD					MIXED APPLICATION					CYCLIC*		
		mm	mm					10	20	30	40 to 65	70	15	30	
IF 600/70R34	DW20 DW21	605 23.8	1708 67.2	777 30.6	5086 200.2	160D	bar	6	12	19	25 to 40	43	9	19	
							psi	86	172	273	360	620	124	273	
							Speed	3840	3260	3140	3020	2750	3470	3310	
							Symbol	12	8460	7180	6920	6650	6060	7640	7290
								1	4370	3720	3580	3440	3130	3960	3770
								15	9630	8190	7890	7580	6890	8720	8300
								1.2	4860	4140	3980	3830	3490	4400	4190
								1.7	10700	9120	8770	8440	7690	9690	9230
								1.4	5320	4530	4360	4190	3810	4820	4590
								20	11720	9980	9600	9230	8390	10620	10110
	1.6	5750	4890	4710	4530	4120	5210	4960							
	23	12670	10770	10370	9980	9070	11480	10930							

All tires confirms ETRTO T&RA & STRO standards