

<b>Main Features</b>	<ul style="list-style-type: none"> <li>● <b>Completely New Look</b> Designed with worm gear transmission, completely new look, mini size.</li> <li>● <b>1080P Full HD</b> Apply Panasonic's 1/2.7 inch, 2.07 million effective pixels high quality HD CMOS sensor, can reach maximum 1920 x 1080 high resolution and achieve quality image.</li> <li>● <b>Ultra-high Frame Rate</b> The output frame rate up to 60fps in 1080P.</li> <li>● <b>72.5° Wide-angle Lens + 16x Digital Zoom</b> Use 72.5° wide-angle high quality lens, support 12x optical zoom, and 16x digital zoom.</li> <li>● <b>Low-light</b> High SNR of CMOS sensor combined with 2D and 3D noise reduction algorithm, effectively reduce the noise, even under low illumination conditions, picture can still keep clean and clear.</li> <li>● <b>Remote Control</b> Using RS232/485 interface, all the parameters of the camera can be remote controlled by the high-speed communications.</li> </ul>
<b>Model</b>	VHD-V71H
<b>Name</b>	HD Video Conference Camera
<b>Camera</b>	
Video System	1080p/60, 1080p/50, 1080i/60, 1080i/50, 1080p/30, 1080p/25, 720p/60, 720p/50, 720p/30, 720p/25
Sensor	1/2.7", CMOS, Effective Pixel: 2.07M
Scanning Mode	Progressive
Lens	12x, f3.5mm ~ 42.3mm, F1.8 ~ F2.8
Digital Zoom	16x
Minimal Illumination	0.5 Lux @ (F1.8, AGC ON)
Shutter	1/30s ~ 1/10000s
White Balance	Auto, 3000K/Indoor, 4000K, 5000K/Outdoor, 6500K_1, 6500K_2, 6500K_3, One Push,
Backlight Compensation	Support
Digital Noise Reduction	2D&3D Digital Noise Reduction
Video S/N	≥55dB
Horizontal Angle of View	72.5° ~ 6.9°
Vertical Angle of View	44.8° ~ 3.9°
Horizontal Rotation Range	±170°
Vertical Rotation Range	-30° ~ +30°
Pan Speed Range	1.7° ~ 100°/s
Tilt Speed Range	0.7° ~ 28°/s
H & V Flip	Support
Image Freeze	Support
Number of Preset	255
Preset Accuracy	0.1°
<b>Input/Output Interface</b>	
HD Interface	1xHDMI: Version 1.3
Network Interface	1xRJ45: 10M/100M Ethernet Interface
Audio Interface	1-ch: 3.5mm Audio Interface, Line In
Communication Interface	1xRS232 In: 8pin Min DIN, Max Distance: 30m, Protocol: VISCA/Pelco-D/Pelco-P
Power Jack	JEITA type (DC IN 12V)
<b>Generic Specification</b>	
Input Voltage	DC 12V
Current Consumption	1.0A (Max)
Operating Temperature	-10°C ~ 40°C (14°F ~ 104°F)
Storage Temperature	-40°C ~ 60°C (-40°F ~ 140°F)
Power Consumption	12W (Max)
MTBF	>30000h
Size	128.5mm x 118.0mm x 156.2mm
Net Weight	0.9 Kg
Product Picture	