


Datasheet

www.vitrum.com

Vitrum I BS Dimmer Classic

cod. 01B010040





2 Wires

CE

FUNCTIONAL SPECIFICATION

- One-button light switch
- Touch control with capacitive technology and concave surface for tactile Feedback
- Acoustic feedback signal
- Crown backlit by low-consumption LEDs

COMMAND MODE

- One capacitive button with "On-Off" contol
- Dimming touch:
- Single short pressure for "On-Off"
- Keeping pressure: light increase from 0 to 100%
 Dimmering by circular touch (iPOD like control)
- (increasing with clockwise touch, decreasing with counterclockwise touch)

MECHANICAL CHARACTERISTICS

- Box British 1 Gang (wall or plasterboard)
- Dimension 95x95mm
- Depht at sight 8 mm
- Operating temperature: 0-40°C
- Button Diameter 38 mmLight ring diameter 42 mm
- Weight: 190 g.

ELECTRICAL CHARACTERISTICS

- Power: 230V ac
 Energy consumption: < 1W
- Energy consumption: < 1W
- 2 wires wiring with load > 40 VA, 3 wires wiring with load <40 VA
- Output power per channel > 20 VA e < 300VA
 - Control of following lamp:
 - incandenscent
 - halogenal
 - fluorescent dimmable (DULUX EL Osram e Philips)
- Universal power control: (trailing / leading edge mode)
- Protection for overload and short circuit
- Power Mosfet Technology

Compliant with:

.

B.T.: 2006/95/CE **E.M.C.:** 2004/108/CE



Think Simple SpA reserves the right to modify its products at any time and without notice in order to better their quality and functionality. Therefore, all the information given in this datasheet is to be considered subject to possible modifications.

Think Simple SpA

CF / P.Iva 01675770935 viale l www.thinksimple.it 3317 info@thinksimple.it Tel +3 support@thinksimple.it Fax +

Head Office

viale Lino Zanussi, 3 33170 Pordenone Tel +39 0434 516 216 Fax +39 0434 516 230

Sales Office

corso Garibaldi, 86 20121 Milano Tel +39 02 655 600 29 Fax +39 02 454 982 95