



**SUPER ELASTI 107**

:  
 ( , , ( , , 100 100 ), )  
 , , ,  
 ( >2%). ( , , , ).  
 :  
 , , , OSB XPS.

OSB, XPS,  
 « »

-50 ° +70 °  
 EN 12004 EN 12002: 2TE S1



( , , ): + 5 ° + 30 ° .

:  
 « - .2.6-212:2016». « - .3.1-23:2013»  
 , , , ,  
 3 , - 4 .  
 3 , KREISEL KALKZEMENT-MASCHINENPUTZ 500  
 (501). KREISEL  
 FLIESS-BODENSPACHTEL 410 (411, 412).  
 ( , , , ) ,  
 KREISEL TIEFGRUND-LMF 301.

: +5 ° +30 ° ) 25 , 8,5 ( )  
 5 .



## SUPER ELASTI 107

45-60 °

80 %

30 30

65 %

48  
KREISEL

12

.1. 4 .2.7-126:2011

25 , 42

126:2011	.2.7-	4
:	:	- 60
:	:	- 20
:	:	- 10
:	:	m0,5



## SUPER ELASTI 107

( ):			
:	- 48		
:			
- :	- 1,0		
- : - :	- 1,0		
- : , 50 - :	- 1,0		
, (+70°):	- 1,0		
:	2-15		
:	Á 1,3 / 2/		
	( )		
		1,	2, / 2
5	3	1,95	
5-10	4	2,6	
10-20	6	3,9	
20	8	5,2	
	10	6,5	
	12	7,8	
1 -			
2 -	0,4 - 0,8 / 2.		

KREISEL SUPER ELASTI 107