

# **FARMAX R85**

#### FEATURE

• Greater lug overlap

#### **BENEFITS**

- More lugs in footprint
- Better stability

#### FEATURE

• Larger inner volume

#### **BENEFITS**

- Reduced soil compaction
- Increased load carrying capacity

#### **FEATURES**

- Reduced space between lugs
- Mud breaker at the centre

#### **BENEFITS**

- Better roadability
- Increased service life
- Self cleaning

#### FEATURE

• Rounded shoulder

#### BENEFIT

• Less soil disturbance

#### FEATURE

• Dual lug angle

#### BENEFITS

- Superior traction
- Better Roadability

### MACHINERY



Tractor

## FEATURE

Wider tread

#### BENEFITS

- Reduced soil compaction
- Increased footprint

Size	LI/SS	Туре	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph /mph					
				sw	OD	JLII	no	IIII. 11633	Static	10	20	30	40	50
									Otatio	6	12	19	25	31
				mm	mm	mm	mm	bar	Recommend load kg /lbs					
				in	in	in	in	psi	necomment road kg / ibs					
460/85R38	149 A8/B	H	W16L W15L W14L	480 18.9	1747 68.8	803 31.6	5213 205.2	0.8	4990	3260	2670	2320	2170	2170
								12	10990	7180	5880	5110	4780	4780
								1	5680	3710	3040	2640	2470	2470
								15	12510	8170	6700	5810	5440	5440
								1.3	6620	4320	3540	3080	2880	2880
								19	14580	9520	7800	6780	6340	6340
								1.6	7480	4880	4000	3480	3250	3250
								23	16480	10750	8810	7670	7160	7160

All tires confirms ETRTO T&RA & STRO standards