



RES SMT 360™ Multi-GNSS Timing Module

KEY FEATURES

- Multi-Constellation
- Simultaneous GPS / GLONASS or GPS / Beidou tracking
- Ideal for populated urban and indoor environments with limited sky-view
- PPS and PP2S outputs, synchronized to GNSS / UTC within 15ns (1 sigma)
- Extended temperature range (-40°C / +85°C)

Miniature Multi-GNSS Timing Module with Super-Sized Features

Ideal for Low Signal Environment

Trimble® designed the RES SMT 360™ Timing Module to work in the most demanding weak signal environments, including femtocells and in-building systems.

With its robust performance in low signal environments, users can save on expensive cabling and externally mounted antennas. In addition, the RES SMT 360™ timing module accepts aiding data for environments requiring the highest levels of enhanced sensitivity.

Timing Signal Outputs

The RES SMT 360™ timing module outputs a precise 1 pulse-per-second (1PPS) and an even second pulse to maximize your network performance and synchronize systems at a global level.

Custom frequencies are also available for volume sale.



Standard Timing Features

The RES SMT 360™ timing module includes many of Trimble's standard timing features, including Time-Receiver Autonomous Integrity Monitoring (T-RAIM) algorithm, automatic self-survey, and GNSS disciplining of the oscillator to provide an accurate frequency reference

Carrier Board and Starter Kit Options

The RES SMT 360™ timing module can be loaded directly onto the customer's application board.

The Starter Kit provides everything you need to evaluate the RES SMT 360™ timing module, including the RES SMT 360™ on a carrier board, AC/DC power converter, antenna and USB interface cable.

RES SMT 360™ Multi-GNSS TIMING MODULE

GENERAL SPECIFICATIONS

Receiving Signal.....GPS, GLONASS, Galileo, Beidou
 Supports GNSS incl.SBAS, QZSS
 Positioning System.....SPS, Timing
 1 PPS Timing Accuracy15 ns (1 sigma)
 Update Rate.....1 Hz
 Typical Min Acq Sensitivity.....-148dBm cold start
 Typical Min Tracking Sensitivity -160dBm
 Time to First Fix.....<46s (50%), <50s (90%) cold start
 Typical Time to Re-acquisition..... <2s (90%)

INTERFACE CHARACTERISTICS

Connections.28 surface-mount edge castellations
 Serial Port.....2 serial port
 PPS / Even Second.....CMOS-compatible
 LVTTTL-level pulse, once per second
 Protocols.....TSIP, NMEA 0183

PINOUT ASSIGNMENTS

RES SMT 360 PINOUTS

GND	1	28	GND
GND	2	27	VCC
RFIN	3	26	GND
GND	4	25	RESET
OPEN	5	24	GND
SHORT	6	23	RESERVED
RESERVED	7	22	TXDB
RESERVED	8	21	RXDB
RESERVED	9	20	GND
RESERVED	10	19	PPS
RESERVED	11	18	GND
RESERVED	12	17	TXDA
RESERVED	13	16	RXDA
GND	14	15	GND

PHYSICAL CHARACTERISTICS

Enclosure.....Metal Shield
 Dimensions19 mm W x 19 mm L x 2.54 mm H
 (0.75" W x 0.75" L x 0.1" H)
 Weight.....1.8 grams (0.06 ounce) including shield

ELECTRICAL CHARACTERISTICS

Supply Voltage Range.....3.3VDC to ±5%
 Power Consumption.....0.5W max.

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature.....-40°C to +85°C
 Operating Humidity.....5%-95% RH non-condensing (+60°C)
 Storage Temperature.....-50°C to +105°C

GENERAL INFORMATION & ACCESSORIES

Module.....available in 20 piece trays for evaluation
 Production quantities on tape on reel (500 pieces)

Reference Board.....GNSS module mounted on a
 carrier board with I/O and RF connectors,
 including RF circuitry with the antenna open
 detection, as well as antenna short detection
 and protection.

Starter KitIncludes Reference Board mounted
 on interface motherboard in a durable metal
 enclosure, AC/DC power converter, Bullet 360
 antenna, USB interface cable, TSIP and NMEA
 protocols

Antenna..... Bullet 360

Visit www.trimble.com/timing for part numbers
 and information about where to buy.

Parts of the product are patent protected.

*Trimble has relied on representations made by its suppliers in certifying this product
 as RoHS-II compliant.*

Specifications subject to change without notice.

ООО "Геопрактик"

г. Харьков, пр-т. Гагарина, 20, офис 1310
 +38(067)179-49-79
 +38(095)179-49-79

office@geopraktik.com

geopraktik.com.ua

АВТОРИЗОВАННЫЙ ДИСТРИБЬЮТОР TRIMBLE

KOREA

Trimble Export Ltd. Korea
 Phone: +82-2-555-5361

CHINA

Trimble Navigation Ltd. China
 Phone: +86-10-8857-7575



www.trimble.com