

# FARMAX R80

**FEATURE**

- Greater lug overlap

**BENEFITS**

- More lugs in footprint
- Better stability

**FEATURE**

- Larger inner volume

**BENEFITS**

- Reduced soil compaction
- Increased load carrying capacity



**FEATURES**

- Reduced space between lugs
- Mud breaker at the centre

**BENEFITS**

- Better roadability
- Increased service life
- Self cleaning

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Less soil disturbance

**FEATURE**

- Dual lug angle

**BENEFITS**

- Superior traction
- Better Roadability


**FEATURE**

- Wider tread

**BENEFITS**

- Reduced soil compaction
- Increased footprint

## MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph / mph					
				SW	OD				Static	10	20	30	40	50
				mm	mm					6	12	19	25	31
				in	in				Recommend load kg / lbs					
380/80R38	142 A8/B	TL	W11 W12 W13	380 15	1573 61.9	731 28.8	4728 186.2	1	3660	2390	1960	1700	1590	1590
								15	8060	5260	4320	3740	3500	3500
								1.6	4810	3140	2570	2240	2090	2090
								23	10590	6920	5660	4930	4600	4600
								2	5470	3570	2930	2550	2380	2380
								29	12050	7860	6450	5620	5240	5240
								2.4	6100	3980	3260	2840	2650	2650
35	13440	8770	7180	6260	5840	5840								