



ALLIANCE
AGRICULTURE

TRA: **R-1W**
Speed Rating: **D**

The Alliance 365 tread pattern represents the family of modern radial agricultural tires with low aspect ratio. High tire volumes as well as low inflation pressure, provides high traction capabilities and more soil protection. The optimum number of elastic lugs promises excellent self cleaning capability. Strong carcass and rigid belts ensure long tire life.

TEXTILE(T) Standard
Compound

For ATC Tires Pvt Limited



Dan Steltmann
Chief Technology Officer



TRACTOR - 540/65R30

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load								
		Speed														
		Non-cyclic operation														
		Static kmph	10 kmph					20 kmph	25 kmph	30 kmph	40 kmph	50 kmph	65 kmph	70 kmph		
540/65R30	17X30 W16LX30, , W18LX30	560	1486	683	4483	150D 153A8	0.8	4140	2700	2210	2130	2070	1970	1890	1800	1640
							1.2	5290	3450	2830	2730	2650	2520	2420	2300	2090
							1.6	6270	4090	3350	3230	3130	2980	2860	2725	2480
							2	7070	4610	3780	3640	3540	3370	3230	3075	2800
							2.4	7710	5030	4120	3970	3850	3650	3520	3350	3050

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load	
		Speed							
		Cyclic operation							
		10 kmph	15 kmph						
540/65R30	17X30 W16LX30, , W18LX30	560	1486	683	4483	150D 153A8	1	3060	2790
							1.5	3910	3570
							2	4630	4220
							2.5	5230	4770
							3	5700	5190

For ATC Tires Pvt Limited




Dan Steltmann
 Chief Technology Officer