



**ALLIANCE  
 AGRICULTURE**

TRA: **R-1W**  
 Speed Rating: **D**



STUBBLE  
 GUARD

The high speed 'D' rated AGRI STAR II comes with a Stratified Layer technology (SLT) - a unique combination of two layers: The top layer with a single angle profile and bottom layer with a multi-angle profile. After 40% wear of the tire, bottom layer of the lug comes in contact with the ground which leads to increased contact area at the central portion. This leads to better roadability and performance of the tire. The increased amount of rubber volume in AGRI STAR II enhances its stiffness that results in better wear resistance.

**70 Series - 600/70R30**

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load						
		SW mm	OD mm					Speed						
								Static kmph	10 kmph	25 kmph	30 kmph	40 kmph	50 kmph	65 kmph
600/70R30	DW20Bx30 DW18L W18L	614	1605	706	4710	152D	0.8	5430	3540	2800	2710	2580	2480	2360
							1	6100	3980	3140	3050	2900	2780	2650
							1.2	6900	4500	3560	3450	3290	3150	3000
							1.4	7710	5030	3970	3850	3670	3520	3350
							1.6	8170	5330	4210	4080	3890	3730	3550

Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)

For ATC Tires Pvt Limited



Dan Steltmann  
 Chief Technology Officer

