



ALLIANCE  
**AGRICULTURE**

TRA: **R-1W**  
 Speed Rating: **D**



STUBBLE  
 GUARD

The high speed 'D' rated AGRI STAR II comes with a Stratified Layer technology (SLT) - a unique combination of two layers: The top layer with a single angle profile and bottom layer with a multi-angle profile. After 40% wear of the tire, bottom layer of the lug comes in contact with the ground which leads to increased contact area at the central portion. This leads to better roadability and performance of the tire. The increased amount of rubber volume in AGRI STAR II enhances its stiffness that results in better wear resistance.

**70 Series - 710/70R38**

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load						
		SW mm	OD mm					Speed						
								Static kmph	10 kmph	25 kmph	30 kmph	40 kmph	50 kmph	65 kmph
710/70R38	DW23Bx38 DW25B	720	1959	885	5781	172D	0.8	7710	5030	3970	3850	3670	3520	3350
							1	8910	5810	4590	4460	4240	4070	3875
							1.6	12190	7950	6280	6100	5800	5570	5300
							2	13340	8700	6870	6670	6350	6090	5800
							2.4	14490	9450	7470	7250	6900	6620	6300
						178D	0.8	7710	5030	3970	3850	3670	3520	3350
							1.4	11210	7310	5780	5610	5340	5120	4875
							2.1	13800	9000	7110	6900	6570	6300	6000
							2.8	15870	10350	8180	7940	7560	7250	6900
							3.4	17250	11250	8890	8630	8210	7880	7500

Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%).

For ATC Tires Pvt Limited



Dan Steltmann  
 Chief Technology Officer

