



**ALLIANCE
 AGRICULTURE**

TRA: **IMP**
 Speed Rating: **A8**

A 320 Value Plus is specially designed for agricultural implements. Its large footprint high rubber to void ratio minimizes soil compaction. Strong textile construction ensures optimal performance and long tire life. This tire can be used on roads and also for grassland and sensitive soil applications in the fields.

IMPLEMENT - 10.0/75-15.3

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load									
		SW mm	OD mm					Speed									
								Drive wheel					Free rolling				
								Static kmph	10 kmph	25 kmph	30 kmph	40 kmph	Static kmph	10 kmph	25 kmph	30 kmph	40 kmph
10.0/75-15.3	9	264	760	343	2243	10PR	3.9	2560	1405	1165	1090	981	2560	1999.5	1660	1550	1395
						129A6 125A8	5.3	NA	NA	NA	NA	NA	3070	2400	1980	1850	1650
						14PR	5.5	3100	1700	1410	1320	1188	3135	2450	2030	1900	1710
						136A6 132A8	7.5	NA	NA	NA	NA	NA	3760	2945	2430	2240	2000

Highlighted rows indicate cyclic high load variations. When tires equip vehicles subject to haulage cyclic high load variations excluding transport application on long distances, i.e. vehicles used on round trips (e.g. from field to farm) where on one way the vehicle is empty & on the other way the gross vehicle mass exceeds two times the mass of empty vehicle (last two rows in the table). Please note that the PR/LI corresponds to the HLV.

For ATC Tires Pvt Limited



Dan Steltmann
 Chief Technology Officer

