



ALLIANCE  
**AGRICULTURE**

TRA: **IMP**  
Speed Rating: **A8**

A 320 Value Plus is specially designed for agricultural implements. Its large footprint high rubber to void ratio minimizes soil compaction. Strong textile construction ensures optimal performance and long tire life. This tire can be used on roads and also for grassland and sensitive soil applications in the fields.

For ATC Tires Pvt Limited



Dan Steltmann  
Chief Technology Officer



**IMPLEMENT - 11.5/80-15.3**

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load									
								Speed									
		Drive wheel						Free rolling									
		Static kmph	10 kmph					25 kmph	30 kmph	40 kmph	Static kmph	10 kmph	25 kmph	30 kmph	40 kmph		
11.5/80-15.3	9	290	845	372	2456	14PR	4.75	3995	2195	1820	1700	1530	4009.5	3134.7	2600.1	2430	2187
						145A6 141A8	6.5	NA	NA	NA	NA	NA	4810	3765	3110	2900	2575

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load				
								Speed				
		Free Rolling										
		Static kmph	10 kmph					25 kmph	30 kmph	40 kmph		
11.5/80-15.3	9x15.3	290	845	366.45	2527	10PR	2	2790	2180	1810	1690	1520
						137A6 133A8	2.5	3180	2490	2070	1930	1740
						3.4	3800	2970	2460	2300	2070	

Highlighted rows indicate cyclic high load variations. When tires equip vehicles subject to haulage cyclic high load variations excluding transport application on long distances, i.e. vehicles used on round trips (e.g. from field to farm) where on one way the vehicle is empty & on the other way the gross vehicle mass exceeds two times the mass of empty vehicle (last two rows in the table). Please note that the PR/LI corresponds to the HLV.

For ATC Tires Pvt Limited




Dan Steltmann  
 Chief Technology Officer