



ALLIANCE
AGRICULTURE

TRA: **IMP**
 Speed Rating: **A8**

A 320 Value Plus is specially designed for agricultural implements. Its large footprint high rubber to void ratio minimizes soil compaction. Strong textile construction ensures optimal performance and long tire life. This tire can be used on roads and also for grassland and sensitive soil applications in the fields.

IMPLEMENT - 16.0/70-20

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load				
		SW mm	OD mm					Speed				
								Free rolling				
								Static kmph	10 kmph	25 kmph	30 kmph	40 kmph
16.0/70-20	13.00x20	418	1075	458.5	3158	12PR	2	5030	3930	3260	3050	2750
						155A6	2.5	5740	4490	3720	3480	3130
							3	6390	5000	4150	3875	3490

When tires equip vehicles subject to haulage cyclic high load variations excluding transport application on long distances, i.e. vehicles used on round trips (e.g. from field to farm) where on one way the vehicle is empty & on the other way the gross vehicle mass exceeds two times the mass of empty vehicle (last two rows in the table). Please note that the PR/LI corresponds to the HLV.

For ATC Tires Pvt Limited



Dan Steltmann
 Chief Technology Officer

