


Vertical display cooler




+2/+7°C

A C



CR 800
770 x 790 x 2080
783lt



Advantages

- Ideal for the conservation and promotion of bottled and packed products.
- Top cooling capacity ideal for perishable products.
- Selected by leading companies in the dairy and beverage sector
- Ideal for heavy duty and outdoors use.
- Shelving solutions suitable for each customer's needs.
- Reliable and functional
- Optimum product visibility.
- Plug ready



Basic Equipment

- Hi efficiency compressor
- Digital controller
- EMD - Energy Management Device
- EBD electronic fan motor (evaporator)
- Self closing doors
- Led Internal lighting
- Operation switch
- Four castors
- 5 adjustable reinforced shelves
- Special antidazzle double glass
- Easily removable grill
- Air cooled condenser
- Two regulators
- Automatic defrost
- Drainage
- Internal body from non toxic pre painted steel sheet



Optional Equipment

- Shelves
- Product labeling and price tags
- EBD electronic fan motor (compressor)
- Branding



Technical Specifications

TECHNICAL SPECIFICATIONS	UNITS	CR 800
External dimensions (lxwxh)	mm	770 x 790 x 2080
Internal dimensions (lxwxh)	mm	690 x 695 x 1635
Packing dimensions (lxwxh)	mm	780 x 800 x 2170
Internal gross volume	lt	783
Capacity of 330ml cans	pcs	-
Temperature range	°C	+2 / +7
Gross / net weight	kg	137 / 128
Climate class	-	CC2/K2
Pieces per truck 13.6m	-	51
Pieces per 20/40'ft container	-	21 / 45
Refrigeration	-	AIR COOLED
Refrigerant	-	R290/R600a

*The energy consumption concerns specific metrics