

* PRODUCT INFORMATION *

HUSKEY™ MP-2 POLYUREA GREASE

DESCRIPTION:

HUSKEY MP-2 Polyurea Grease is a second generation polyurea grease. This unique new, high performance, multi-purpose grease is based on advanced polyurea technology. It is formulated from pure petroleum base oils then fortified with extreme pressure additives and rust and oxidation inhibitors. **HUSKEY MP-2 Polyurea Grease** gives longer bearing life under high speed, high temperature and high water applications than most other widely used antifriction bearing greases. The distinctive Green color makes it easy to identify during and after lubrication.

USAGE:

HUSKEY MP-2 Polyurea Grease is suited for many demanding jobs in the industrial, agricultural, automotive and off-road equipment. It is designed as a multi-service grease for construction equipment, paper and steel mills, conveyers, die pins, electric motors, high speed antifriction bearings and many other applications that require long lasting lubricant protection.

HUSKEY MP-2 Polyurea Grease is an excellent choice for automotive applications. It is recommended for wheel bearings that must withstand heat generated by disc brakes. It is an ideal chassis and CV joint lubricant because of its low temperature properties, shear stability and water resistance capabilities. **HUSKEY MP-2 Polyurea Grease** meets NLGI certification GC-LB.

BENEFITS:

- Long life at high temperatures.
- High extreme pressure characteristics.
- Excellent rust protection.
- Excellent water resistance
- Friendly to copper containing components at high temperature.
- Excellent low temperature properties.
- Environmentally friendly. Contains no heavy metals or chlorine compounds.
- Compatible with many seal materials such as Neoprene, Nitrile, Hytel and Silicone.
- Recommended for "Sealed for Life" applications.



HUSKEY Specialty Lubricants

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

Western Region Office:

1580 Industrial Avenue, Norco, California 92860
(909) 340-4000 • Fax: (909) 340-4011
(888) 4-HUSKEY • www.huskey.com

Eastern Region Office:

8300 Corporate Park Drive, Macedonia, Ohio 44056
(330) 425-2567 • Fax: (330) 425-9637
(800) 238-LUBE

* PRODUCT INFORMATION *

TYPICAL PROPERTIES

DESCRIPTION: **HUSKEY** Product: MP-2 Polyurea Grease
Color: Aqua Green
Thickener: Polyurea
NLGI No: 2
Texture: Smooth

TEST	ASTM TEST METHOD	TEST RESULTS
Penetration:		
Worked (60 Strokes @77°F)	D-217	265 - 295
Dropping Point, °C (°F)	D-2265	260 (500)
Oil Separation, % Loss Max.	D-1742	0.3
Rust Protection	D-1743	Pass
Copper Corrosion	D-4048	1b
Timken OK Load	D-2509	60 lbs.
4 Ball EP Weld Point, Kgs.	D-2596	400
Load Wear Index	D-2596	50
Water Washout, % Loss Max.	D-1264	2.0
Base Oil Viscosity,	D-445	
@ 40°C (cSt)		129
@ 100°C (cSt)		11.6
Flash Point, °C (°F)	D-92	245 (473)
Pour Point, °C (°F)	D-97	-34 (-30)

PACKAGE AVAILABILITY

Convenient disposable gun-loader 14 oz. Cartridges,
1-gal. Pail, 5-gal. Pail, 15-gal. Keg, and 55-gal. Drum

The name of this product or group of products is for product identification only. HUSK-ITT CORPORATION makes no warranties, representations or conditions of any kind expressed or implied, whether for merchantability or fitness with respect to these products. The final determination of the suitability of the products for the application contemplated by the user is the sole responsibility of the buyer. HUSK-ITT CORPORATION sales personnel are not authorized to amend this warranty limitation. 07/16



HUSKEY Specialty Lubricants

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

Western Region Office:

1580 Industrial Avenue, Norco, California 92860
(909) 340-4000 • Fax: (909) 340-4011
(888) 4-HUSKEY • www.huskey.com

Eastern Region Office:

8300 Corporate Park Drive, Macedonia, Ohio 44056
(330) 425-2567 • Fax: (330) 425-9637
(800) 238-LUBE