



# WP-T2C

## Thermal Receipt Printer

- Easy paper loading
- Compatible with ESC/POS
- Support NV LOGO download and printing
- Support multiple 1D barcodes printing
- High speed, long lifetime, high quality



Store



Hospital



Café





Logistics





# WP-T2C

## Thermal Receipt Printer



<b>Printing</b>		WP-T2C
Printing method	Direct thermal	
Paper width	57.5±0.5mm φ60mm	
Print width	48 mm	
Column capacity	384 dots/line	
Printing speed	90 mm/s	
Interface	USB/ Parallel/ USB+Bluetooth(6+7)	
Line spacing	3.75mm (Adjustable by commands)	
<b>Fonts Symbologies</b>		
Character size	ANK,Font A: 12*24 dots; Font B: 9*17 dots; CHN: 24*24 dots	
Extension character sheet	PC347(Standard Europe) / Katakana/ PC850(Multilingual) / PC860(Portuguese) / PC863 (Canadian-French) / PC865(Nordic) / West Europe/ Greek/ Hebrew/ East Europe/ Iran/ WPC1252/ PC866(Cyrillic#2) / PC852(Latin2)/ PC858/ IranIII/ Latvian/ Arabic/ PT151(1251)	
Barcode types	UPC-A / UPC-E / JAN13(EAN13) / JAN8(EAN8) / CODE39 / ITF / CODABAR / CODE93 / CODE128	
Input buffer	32 Kbytes	
NV Flash	64 Kbytes	
<b>Power</b>		
Power adaptor	Input: AC 110V/220V, 50~60Hz; Output: DC 12V/2.6A	
Printer voltage	Input: DC 12V/2.6A	
Cash drawer	DC 12V/1A	
<b>Physical characteristics</b>		
Weight	0.55 KG	
Dimensions	181*130*108mm(D*W*H)	
<b>Environmental Requirements</b>		
Work environment	Temperature (0~45°C); humidity(10~80%)	
Storage environment	Temperature(-10~60°C); humidity(10~90%)	
<b>Reliability</b>		
Printer head life	50KM	
<b>Systems</b>		Windows/Linux



Guangzhou Winprt Technology Co., Ltd.  
 Address: Room 614,NO.80 JinGang Road,  
 Nansha District, Guangzhou, Guangdong, China.  
<http://www.winprt.com>  
 Email:overseas@winprt.com

