



PRINT THIS PAGE

3000 rpm 50 Hz – $\cos \phi$ 0,8 230V – 400/230V 3600 rpm 60 Hz – $\cos \phi$ 0,8 voltage on request

LAMPO QUIET SERIES








STANDARD EQUIPMENT

- Soundproof canopy
- Exhaust gas silencer
- Air filter
- Fuel tank
- Key start switch
- Distribution panel with output sockets with circuit breaker, 0,03 A ELCB optional
- 12V Battery

GASOLINE Air Cooled

LAMPO QUIET SERIES


MODEL	kVA max	kVA cont	kVA max	kVA cont	Starting	Brand		Cylinder	cm3	Hp (max) 3600	Cons. 75%(h/l)	Standard panel	Automatic panel					Engine Technical Data			
	50 Hz	60 Hz	Tank l	L														W	H	Kg	LWA (•)
SINGLE-PHASE																					
GS5000HMPE	4,5	4,1	5,4	5	E	Honda	GX270	1	20	9	1,5	QM132	QS32 ATS	7	94	51	55	106	88		
GS7000HMPE	7.2	6.5	8	7.2	E	Honda	GX390	1	389	13	1.9	QM133	QS32 ATS	15	110	54	65	140	88		
GS12010HMPE	11	10	--	--	E	Honda	GX630	2	688	20.8	4	QM107	QS32 ATS	20	107	56	93	190	88		
GS13010HMPE	13	12	--	--	E	Honda	GX690	2	688	22.1	7	QM107	QS32 ATS	20	107	56	93	210	88		
THREE-PHASE																					
GS8000HTPE	7.5	6.8	8.3	7.5	E	Honda	GX390	1	389	13	1.9	QM330	QS32 ATS	15	110	54	65	140	88		
GS12510HTPE	11	10	--	--	E	Honda	GX630	2	688	20.8	4	QM307	QS32 ATS	20	107	56	93	190	88		
GS13510HTPE	13	12	--	--	E	Honda	GX690	2	688	22.1	7	QM307	QS32 ATS	20	107	56	93	210	88		

Edit Table

Legend: (•) = Tested value; noise level compliant with European regulation 2000/14/CE

> CONTROL PANEL

QM 132




QM 133




QM 330




QM 107



QM307



QS32ATS



BRUNO SRL

S.S. 91 Km 0,600 – 83035 Grottaminarda (AV) –
ITALY | VAT IT 01713250643

ITALY SALES DEPARTMENT

Tel: +39 0825 421035

Fax:+39 0825 421654

E mail:venditeitalia@brunogenerators.it

EXPORT DEPARTMENT

Tel. +39.0825.421005

Fax.+39.0825.426169

export@brunogenerators.it