


SKM 150GB128D



SEMITRANS™ 3

SPT IGBT Modules

www.DataSheet4U.com

SKM 150GB128D

Preliminary Data

Features

- Homogeneous Si
- SPT = Soft punch-through technology
- V_{CEsat} with positive temperature coefficient
- High short circuit capability, self limiting to $6 \times I_C$

Typical Applications







- AC inverter drives
- UPS
- Electronic welders at f_{sw} up to 20 kHz









GB




Absolute Maximum Ratings		$T_c = 25\text{ °C}$, unless otherwise specified	
Symbol	Conditions	Values	Units
IGBT			
V_{CES}		1200	V
I_C	$T_c = 25\text{ (80) °C}$	200 (140)	A
I_{CRM}	$T_c = 25\text{ (80) °C}$, $t_p = 1\text{ ms}$	400 (280)	A
V_{GES}		± 20	V
T_{vj} (T_{stg})	$T_{OPERATION} \leq T_{stg}$	- 40 ... + 150 (125)	°C
V_{isol}	AC, 1 min.	4000	V
Inverse diode			
$I_F = -I_C$	$T_c = 25\text{ (80) °C}$	150 (100)	A
I_{FRM}	$T_c = 25\text{ (80) °C}$, $t_p = 1\text{ ms}$	400 (280)	A
I_{FSM}	$t_p = 10\text{ ms}$; sin.; $T_j = 150\text{ °C}$	1100	A

Characteristics		$T_c = 25\text{ °C}$, unless otherwise specified			
Symbol	Conditions	min.	typ.	max.	Units
IGBT					
$V_{GE(th)}$	$V_{GE} = V_{CE}$; $I_C = 4\text{ mA}$	4,5	5,5	6,5	V
I_{CES}	$V_{GE} = 0$, $V_{CE} = V_{CES}$; $T_j = 25\text{ (125) °C}$		0,2	0,6	mA
$V_{CE(TO)}$	$T_j = 25\text{ (125) °C}$		1 (0,9)	1,15 (1,05)	V
r_{CE}	$V_{GE} = 15\text{ V}$, $T_j = 25\text{ (125) °C}$		9 (12)	12 (15)	mΩ
$V_{CE(sat)}$	$I_C = 100\text{ A}$, $V_{GE} = 15\text{ V}$, chip level		1,9 (2,1)	2,35 (2,55)	V
C_{ies}	under following conditions		8,1		nF
C_{oes}	$V_{GE} = 0$, $V_{CE} = 25\text{ V}$, $f = 1\text{ MHz}$		1,2		nF
C_{res}			1,1		nF
L_{CE}				20	nH
$R_{CC'+EE'}$	res., terminal-chip $T_c = 25\text{ (125) °C}$		0,35 (0,5)		mΩ
$t_{d(on)}$	$V_{CC} = 600\text{ V}$, $I_C = 100\text{ A}$		80		ns
t_r	$R_{Gon} = R_{Goff} = 8\text{ Ω}$, $T_j = 125\text{ °C}$		40		ns
$t_{d(off)}$	$V_{GE} = \pm 15\text{ V}$		460		ns
t_f			65		ns
$E_{on} (E_{off})$			10 (9)		mJ
Inverse diode					
$V_F = V_{EC}$	$I_F = 100\text{ A}$; $V_{GE} = 0\text{ V}$; $T_j = 25\text{ (125) °C}$		2 (1,8)	2,5 (2,3)	V
$V_{(TO)}$	$T_j = 25\text{ (125) °C}$		1,1	1,45 (1,25)	V
r_T	$T_j = 25\text{ (125) °C}$		9	13 (11)	mΩ
I_{RRM}	$I_F = 100\text{ A}$; $T_j = (125)\text{ °C}$		(145)		A
Q_{rr}	$di/dt = 3600\text{ A/μs}$		(16,5)		μC
E_{rr}	$V_{GE} = 0\text{ V}$		(5,5)		mJ
Thermal characteristics					
$R_{th(j-c)}$	per IGBT			0,15	K/W
$R_{th(j-c)D}$	per Inverse Diode			0,3	K/W
$R_{th(c-s)}$	per module			0,038	K/W
Mechanical data					
M_s	to heatsink M6	3		5	Nm
M_t	to terminals M6	2,5		5	Nm
w				325	g





SKM 150GB128D



This is an electrostatic discharge sensitive device (ESDS), international standard IEC 60747-1, Chapter IX.

This technical information specifies semiconductor devices but promises no characteristics. No warranty or guarantee expressed or implied is made regarding delivery, performance or suitability.