

Choetech Powerstation Specifiation

Powerstation	Product picture	
	Specifi	300w
	shell material	ABS+PC
	Battery Type	Ternary Lithium 18650
	battery brand	Yiwei Lithium Energy
	Output power (W)	300
	Peak power (W)	600
	Energy storage capacity (Wh)	277
	Energy Storage mAh/Voltage	76800mAh/3.6V
	Energy storage ampere/voltage	25.6Ah/10.8V
	Product size (mm)	248*164*169
	Packing size Inner box (mm)	375*215*246
	UN box size Outer box (mm)	450*389*274
	Product net weight (kg)	3,7
	Gross weight (kg)	5,4
	Number of units/carton	2
	Номер карток (Card board 1m*1m)	72pcs (36CTNs, 6*6stacked)
	Номер карток (Card board 1m*1.2m)	72pcs (36CTNs, 6*6stacked)
	Quantity/20ft container (1m*1m card board)	10pallets - 720pcs
	Quantity/40ft container (1m*1.2m pallet)	20pallets-1440pcs
	AC output	US/JP: 100V-120V 50Hz/60Hz EU/UK: 230V 50Hz CH: 220V 50Hz KR: 220V 60Hz AUS: 240V 50Hz
	AC AC output interface	110v*2 220v*1

Output	PD output	100W*1
	QC output	18W*2
	USB-A output	5V/2.4A*2
	Cigarette lighter hole output	12V/10A
	XT60 output	/
	DC output	12V/8A
	Bypass conversion	N/A
	UPS функція	N/A
	Car battery charging	N/A
	battery pack	N/A
Input	AC input (W)	Adapter60W/PD-100W
	AC charging time (H)	Around 5hrs/3hrs
	PD input (W)	100W
	PD charging time (H)	Around 3.5 hrs
	Solar input (W) Андерсон	80W Max
	Solar charging time (H)	Around 4 години
	Car cigarette lighter input (A)	4A (48w)
	Car cigarette lighter charging time (H)	Around 7 hrs
	AC+PD charging time	Simultaneous charging for about 1.6 hrs
	AC+Solar charging	/
Temperature	charging temperature	0-40℃
	Operating temperature	-10-40℃
Protection mechanism	Overcurrent protection Overvoltage protection Overload protection Overcharge protection Over discharge protection Short circuit protection	Overcurrent protection Overvoltage protection Overload protection Overcharge protection Over discharge protection Short circuit protection
LED	Steady on, SOS, Blinking	Steady on, SOS, Blinking
app (bluetooth)		
Screen	Display	LCD
Accessories	Accessories	Adapter, manual