



POWER SUPPLY;
 PHASES:1;
 PN(KW):0,36;
 UPRI(V):400-230+/-15;
 USEC(V DC):24;
 ISEC(A DC):15/18 (60/40 CEL);
 F(HZ):50...60;
 VECTOR GR./SHIELD WNG.:II0 /0;
 PROTECTION CL.:I;
 TA/ISOKL:60 /B;
 W(%):5;
 IP00;
 TYPE OF TERMINALS:SCREW CONNECTION;
 INSTALLATION:SCREW;
 EN 61558-2-6,
 EN61131-2 >SAFETY ISOLATING TRANSFORMER<

General technical details:

product designation	4AV2600-2EB00-0A
product brand name	SIDAC
Connection symbol	li0
Verification of suitability	CE
Product function	
<ul style="list-style-type: none"> • temperature surveillance 	No
<ul style="list-style-type: none"> • isolation control 	No
<ul style="list-style-type: none"> • short circuit and overload protection 	No
<ul style="list-style-type: none"> • varistor protective wiring 	Yes
Operating resource protection class	I
Number of the protective coils	0

Inputs:

Phase number / of the inputs	1
Type of current / of the inputs	AC
Input voltage	
<ul style="list-style-type: none"> • _1 / rated value 	V 415
<ul style="list-style-type: none"> • _2 / rated value 	V 400
<ul style="list-style-type: none"> • _3 / rated value 	V 385
<ul style="list-style-type: none"> • _4 / rated value 	V 245

• U_5 / rated value	V	230
• U_6 / rated value	V	215
Electrical input frequency		
• minimum	Hz	50
• maximum	Hz	60
Input voltage		
• minimum	V	193.5
• maximum	V	439.9
Input current		
• I_1 / rated value	A	1.55
• I_2 / rated value	A	1.6
• I_3 / rated value	A	1.65
• I_4 / rated value	A	2.7
• I_5 / rated value	A	2.8
• I_6 / rated value	A	2.9
Design of the electrical connection / at the input / for main current circuit		screw-type terminals

Outputs:

Type of current		DC
• I_1 / secondary side		
Output voltage		
• U_1 / rated value	V	24
Output voltage / of the measured value signal / at the analog output / for DC / maximum	V	28.8
Output voltage / of the measured value signal / at the analog output / for DC / minimum	V	20.4
Output current		
• I_1 / rated value	A	15
Design of the electrical connection / secondary side / for main current circuit		screw-type terminals
Relative residual ripple		
• of the output voltage U_1 / for main current circuit / maximum	%	5

Ambient conditions:

Thermal class / according to IEC 60085		B
Ambient temperature / rated value	°C	60
Protection class IP		IP00

Mechanical design:

Type of mounting		screws
Construction form of the iron core		EI 150/48

Width	m	150
Height	m	200
Depth	m	140

Certificates/approvals:

General Product Approval	other	
ROSTEST	Manufacturer	other

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

CAX-Online-Generator

<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/4AV2600-2EB00-0A/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=4AV2600-2EB00-0A

last change:

May 16, 2011