
MODEL
W8F

Ninety degree, panel mount
CAVITY: T-10A

sunhydraulics.com/model/W8F



TECHNICAL DATA

Body Type	Line mount
Interface	None
Body Features	Ninety degree, panel mount
Mounting Hole Thread	M5x.08 - 6H
Mounting Hole Depth	.38 in.
Mounting Hole Quantity	4

CONFIGURATION

/S Modifier — 65-45-12 Ductile Iron, Buna-N, Chem. Black

NOTES

Important: Carefully consider the maximum system pressure. The pressure rating of the manifold is dependent on the manifold material, with the port type/size a secondary consideration. Manifolds constructed of aluminum are not rated for pressures higher than 3000 psi (210 bar), regardless of the port type/size specified.

PORT DESIGNATORS

Modifiers	Ports
W8F, /10, /11	All Ports: 1/4" BSPP;

CONFIGURATION OPTIONS
Model Code Example: W8F/S

MODIFIER (/S)

/S 65-45-12 Ductile Iron, Buna-N, Chem. Black
6061-T651 Aluminum, Buna-N
/11 6061-T651 Aluminum, Buna-N, Clear Anodize - Per MIL SPEC 8625F Type II, Class I
/10 6061-T651 Aluminum, Buna-N, Black Anodize - Per MIL SPEC 8625F Type II, Class II
/S3 65-45-12 Ductile Iron, Buna-N, Trivalent Clear Zinc with Top Sealer

© 2023 Sun Hydraulics