

MODEL
PBHB

Pilot-operated, pressure reducing valve
SERIES 3 / CAPACITY: 40 gpm / CAVITY: T-17A

snhy.com/PBHB





Pilot-operated, pressure reducing valves reduce a high primary pressure at the inlet (port 2) to a constant reduced pressure at port 1, allowing circuits with multiple pressure requirements to be operated using a single pump.

CONFIGURATION

L	Control	Standard Screw Adjustment
W	Adjustment Range	150 - 4500 psi (10,5 - 315 bar), 200 psi (14 bar) Standard Setting
N	Seal Material	Buna-N
(none)	Material/Coating	Standard Material/Coating

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Factory Pressure Settings Established at	blocked control port (dead headed)
Maximum Operating Pressure	5000 psi
Control Pilot Flow	15 - 20 in³/min.
Adjustment - No. of CW Turns from Min. to Max. setting	5
Locknut Hex Size	9/16 in.
Locknut Torque	80 - 90 lbf in.
Seal kit - Cartridge	Buna: 990017007
Seal kit - Cartridge	EPDM: 990017014
Seal kit - Cartridge	Polyurethane: 990017002
Seal kit - Cartridge	Viton: 990017006

NOTES

Maximum pressure differentials for spring ranges: A and B are 3000 psi (210 bar) N and Q are 2000 psi (140 bar) W is 5000 psi (350 bar)inlet pressure

CONFIGURATION OPTIONS

Model Code Example: PBHBLWN

CONTROL (L)

- **L** Standard Screw Adjustment
- **C** Tamper Resistant - Factory Set
- **K** Handknob
- **W** Hex Wrench Adjustment
- **Y** Tri-Grip Handknob

ADJUSTMENT RANGE (W)

- **W** 150 - 4500 psi (10,5 - 315 bar), 200 psi (14 bar) Standard Setting
- **A** 100 - 3000 psi (7 - 210 bar), 200 psi (14 bar) Standard Setting
- **B** 50 - 1500 psi (3,5 - 105 bar), 200 psi (14 bar) Standard Setting
- **N** 60 - 800 psi (4 - 55 bar), 200 psi (14 bar) Standard Setting
- **Q** 60 - 400 psi (4 - 28 bar), 200 psi (14 bar) Standard Setting

SEAL MATERIAL (N)

- **N** Buna-N
- **E** EPDM
- **V** Viton

MATERIAL/COATING

- Standard Material/Coating
- **/AP** Stainless Steel, Passivated
- **/LH** Mild Steel, Zinc-Nickel

© 2019 Sun Hydraulics