

MODEL
RDDA

Direct-acting relief valve
SERIES 1 / CAPACITY: 25 gpm / CAVITY: T-10A

snhy.com/RDDA





CONFIGURATION

L	Control	Standard Screw Adjustment
C	Adjustment Range	1000 - 6000 psi (70 - 420 bar), 1000 psi (70 bar) Standard Setting
N	Seal Material	Buna-N
(none)	Material/Coating	Standard Material/Coating

Direct-acting relief cartridges are normally closed, pressure-limiting valves used to protect hydraulic components from pressure transients. When the pressure at the inlet (port 1) reaches the valve setting, the valve starts to open to tank (port 2), throttling flow to limit the pressure rise. These valves are smooth and quiet, essentially zero leak, dirt tolerant, immune to silting and are very fast.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Cavity	T-10A
Series	1
Capacity	25 gpm
Factory Pressure Settings Established at	4 gpm
Maximum Operating Pressure	5000 psi
Maximum Valve Leakage at Reseat	10 drops/min.
Response Time - Typical	2 ms
Reseat	>90% of setting
Adjustment - No. of CW Turns from Min. to Max. setting	6
Valve Hex Size	7/8 in.
Valve Installation Torque	30 - 35 lbf ft
Adjustment Screw Internal Hex Size	5/32 in.
Locknut Hex Size	9/16 in.
Locknut Torque	80 - 90 lbf in.
Seal kit - Cartridge	Buna: 990310007
Seal kit - Cartridge	EPDM: 990310014
Seal kit - Cartridge	Viton: 990310006
Model Weight	0.37 lb.

CONFIGURATION OPTIONS

Model Code Example: RDDALCN

CONTROL (L)

- **L** Standard Screw Adjustment
- **C** Tamper Resistant - Factory Set
- **Y** Tri-Grip Handknob

ADJUSTMENT RANGE (C)

- **C** 1000 - 6000 psi (70 - 420 bar), 1000 psi (70 bar) Standard Setting
- **A** 500 - 3000 psi (35 - 210 bar), 1000 psi (70 bar) Standard Setting
- **W** 800 - 4500 psi (55 - 315 bar), 1000 psi (70 bar) Standard Setting
- **B** 300 - 1500 psi (20 - 105 bar), 1000 psi (70 bar) Standard Setting
- **D** 200 - 800 psi (14 - 55 bar), 400 psi (28 bar) Standard Setting
- **E** 100 - 400 psi (7 - 28 bar), 200 psi (14 bar) Standard Setting
- **S** 50 - 200 psi (3,5 - 14 bar), 100 psi (7 bar) Standard Setting

SEAL MATERIAL (N)

- **N** Buna-N
- **E** EPDM
- **V** Viton

MATERIAL/COATING


- Standard Material/Coating
- **/AP** Stainless Steel, Passivated
- **/LH** Mild Steel, Zinc-Nickel


© 2019 Sun Hydraulics


TECHNICAL FEATURES


- All 2-port relief cartridges (except pilot reliefs) are physically and functionally interchangeable (same flow path, same cavity for a given frame size).
- Will accept maximum pressure at port 2; suitable for use in cross port relief circuits.
- The seals on the adjust screw are exposed to system pressure which means this valve can only be adjusted when the pressure is removed. The setting procedure is; check the setting, remove the pressure, adjust the valve, check the new setting.
- Valve is relatively insensitive to varying oil temperatures and oil borne contamination.
- Select a spring range where the desired relief setting is approximately mid-range to high between the minimum and maximum pressure to ensure maximum valve repeatability.
- Suitable for use in load holding applications.
- Back pressure on the tank port (port 2) is directly additive to the valve setting at a 1:1 ratio.
- Cartridges configured with EPDM seals are for use in systems with phosphate ester fluids. Exposure to petroleum based fluids, greases and lubricants will damage the seals.
- Incorporates the Sun floating style construction to minimize the possibility of internal parts binding due to excessive installation torque and/or cavity/cartridge machining variations.


PERFORMANCE CURVES















© 2019 Sun Hydraulics



RELATED MODELS

- RDDA3 Non-adjustable direct-acting relief valve

© 2019 Sun Hydraulics