




Sun offers replacement seal kits for all cartridge models. These kits include all of the external seals on the cartridge along with installation instructions. Seal kits are available in Buna-N and Viton for all models, along with EPDM and polyurethane for many models. Please note: Converting the external seals from one material to another does not ensure fluid compatibility with that material due to the existence of internal seals within the cartridge.

CARTRIDGE INSTALLATION DATA

Series	3
Cartridge Thread	1"-14 UNS
Valve Hex Size	1 1/4 in.
Valve Installation Torque	150 - 160 lbf ft
Cavity	T-17A
Model Weight	0.01 lb.

NOTES

- Install back-up rings and O-rings as shown in views.
- When installing continuous back-up rings, use the same technique and the same care used to install O-rings.
- When installing cartridge - be sure to torque to recommended value.

USED WITH

CBFA	CBFB	CBFC	CBFD	CBFG	CBFL	CBGA	CBGB	CBGG	CBGH
CBGL	CBGY	CKGB	CKGD	CKGV	CNGD	CNGE	CNHE	COHA	CXGE
CXHC	DKHC	DKHD	DOHC	DOHD	FREA	LKHC	LKHCZ	LOGCZ	LOHA
LOHA8	LOHB	LOHB8	LOHC	LOHCZ	LOHD	LOHD8	LOHO	LOHOZ	LPHA
LPHC	LRHA	LRHC	MBGA	MBGAX	MBGB	MBGBX	MBGG	MBGGX	MBGM
PBHB	PBHB8	PBHC	PBHF	PBHF8	PPHB	PPHB8	PPHC	PPHF	PPHF8
PRHB	PRHR	RSHC	RSHC8	RSHE	RVGA	RVGB	SCGA	SQHB	XHBA
XHCA	XHOA	XHOAE	XHOB	XHOC					

TECHNICAL FEATURES

- The shelf life for this cartridge seal kit is ten years from date of purchase. This date will be printed on the kit packaging.