

MODEL
RSHE

Air-controlled, pilot-operated, balanced piston sequence valve
SERIES 3 / CAPACITY: 60 gpm / CAVITY: T-17A

sunhydraulics.com/model/RSHE





Air-controlled, pilot-operated, balanced piston sequence valves use compressed air over a diaphragm instead of an adjustable spring to control the pressure setting of the valve. The air signal is supplied through a port in the hex-end of the cartridge. They will supply a secondary circuit with flow once the pressure at the inlet (port 1) has exceeded the valve setting. The pressure setting of a sequence valve controls the pressure at port 1 relative to the pressure at the drain (port 3). These valves are insensitive to back pressure at port 2 (sequence), up to the valve setting. They may be used to regulate pressure in place of 2-port relief valves if there is pressure in the return line.

CONFIGURATION

B	Control	External 4-SAE Port
B	Adjustment Range	50 - 1500 psi (3,5 - 105 bar)
N	Seal Material	Buna-N

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Cavity	T-17A
Series	3
Capacity	60 gpm
Pilot Ratio	20:1
Factory Pressure Settings Established at	4 gpm
Maximum Operating Pressure	2000 psi
Maximum Valve Leakage at 110 SUS (24 cSt)	4 in³/min.
Maximum Air Pressure	150 psi
Response Time - Typical	10 ms
Valve Hex Size	1 1/4 in.
Valve Installation Torque	150 - 160 lbf ft
Seal kit - Cartridge	Buna: 990017007
Seal kit - Cartridge	Polyurethane: 990017002
Seal kit - Cartridge	Viton: 990017006
Model Weight	1.32 lb.

CONFIGURATION OPTIONS

Model Code Example: RSHEBBN


CONTROL (B)	ADJUSTMENT RANGE (B)	SEAL MATERIAL (N)
B External 4-SAE Port	**B** 50 - 1500 psi (3,5 - 105 bar)	**N** Buna-N
		V Viton


TECHNICAL FEATURES


- Pilot flow continues to increase as the pressure at port 1 (inlet), relative to the pressure at port 3 (drain), rises above the valve setting.
- Maximum air pilot pressure should not exceed 150 psi (10,5 bar).
- Pressure at port 3 (drain) determines the minimum valve setting and should not exceed 1000 psi (70 bar).
- Capable of providing explosion proof remote control of the pressure setting, the hydraulic setting is directly porportional to the air setting at a ratio of 20:1 (hydraulic:air).
- All 3 port sequence cartridges are physically and functionally interchangeable (i.e. same flow path, same cavity for a given frame size).
- Incorporates the Sun floating style construction to minimize the possibility of internal parts binding due to excessive installation torque and/or cavity/cartridge machining variations.


PERFORMANCE CURVES

© 2019 Sun Hydraulics









© 2019 Sun Hydraulics