

MODEL
RPEC

Pilot-operated, balanced piston relief valve
SERIES 1 / CAPACITY: 25 gpm / CAVITY: T-10A

sunhydraulics.com/model/RPEC





CONFIGURATION

L	Control	Standard Screw Adjustment
Q	Adjustment Range	60 - 400 psi (4 - 28 bar), 200 psi (14 bar) Standard Setting
N	Seal Material	Buna-N
(none)	Material/Coating	Standard Material/Coating

Pilot-operated, balanced-piston relief cartridges are normally closed pressure regulating valves. When the pressure at the inlet (port 1) reaches the valve setting, the valve starts to open to tank (port 2), throttling flow to regulate the pressure. These valves are accurate, have low pressure rise vs. flow, they are smooth and quiet, and are moderately fast.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Factory Pressure Settings Established at	4 gpm
Maximum Operating Pressure	5000 psi
Maximum Valve Leakage at 110 SUS (24 cSt)	2 in³/min.@1000 psi
Response Time - Typical	10 ms
Adjustment - No. of CW Turns from Min. to Max. setting	5
Locknut Hex Size	9/16 in.
Locknut Torque	80 - 90 lbf in.
Seal kit - Cartridge	Buna: 990010007
Seal kit - Cartridge	EPDM: 990010014
Seal kit - Cartridge	Polyurethane: 990010002
Seal kit - Cartridge	Viton: 990010006

NOTES

For Series 1 cartridges configured with an O control (panel mount handknob), a .75 in. (19 mm) diameter hole is required in the panel.

CONFIGURATION OPTIONS

Model Code Example: RPECLQN

CONTROL (L)

- **L** Standard Screw Adjustment
- **C** Tamper Resistant - Factory Set
- **K** Handknob
- **O** Handknob with Panel Mount
- **W** Hex Wrench Adjustment
- **Y** Tri-Grip Handknob

ADJUSTMENT RANGE (Q)

- **Q** 60 - 400 psi (4 - 28 bar), 200 psi (14 bar) Standard Setting
- **A** 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar) Standard Setting
- **W** 150 - 4500 psi (10,5 - 315 bar), 1000 psi (70 bar) Standard Setting
- **B** 50 - 1500 psi (3,5 - 105 bar), 1000 psi (70 bar) Standard Setting
- **C** 150 - 6000 psi (10,5 - 420 bar), 1000 psi (70 bar) Standard Setting
- **N** 60 - 800 psi (4 - 55 bar), 400 psi (28 bar) Standard Setting

SEAL MATERIAL (N)

- **N** Buna-N
- **E** EPDM
- **V** Viton

MATERIAL/COATING

- Standard Material/Coating
- **/AP** Stainless Steel, Passivated
- **/LH** Mild Steel, Zinc-Nickel

© 2019 Sun Hydraulics