

ProPULS 300 C | 320 | 400 | 500



3	MIG/MAG	PULS	DPULS	MMA	WIG	LIFT ARC	INV.	Hand icon	A	V	3~	DC	SYN	MAN
AUT	Graph icon	Spot icon	2-TAKT	4-TAKT	SPOT	SEQUE.	Symbol	VA	M / MIN	Fan icon	Waves icon	Thermometer icon	S	



ProPULS 300 C | 320 | 400 | 500

**TECHNISCHE DATEN TECHNICAL DATA DATOS TÉCNICOS FICHE TECHNIQUE DATI TECNICI TECHNISCHE GEGEVENS DANE TECHNICZNE DADOS TÉCNICOS DATE TEHNICE ТЕХНИЧЕСКИЕ ДАННЫЕ ТЕКНИК БИЛГИЛЕР**

	ProPULS 300 C	ProPULS 320	ProPULS 400	ProPULS 500
50 Hz 60 Hz	400 V	400 V	400 V	400 V
	16 A	16 A	20 A	32 A
	11 kVA	12 kVA	14,5 kVA	27,5 kVA
	0,9	0,9	0,9	0,9
	10 - 300 A	10 - 320 A	10 - 400 A	10 - 500 A
	14,5 - 29 V	14,5 - 30 V	14,5 - 34 V	14,5 - 39 V
	70 V	70 V	63 V	70 V
	40% 300 A / 29,0 V	40% 320 A / 30,0 V	40% 400 A / 34,0 V	40% 500 A / 39,0 V
	60% 230 A / 25,5 V	60% 260 A / 27,0 V	60% 350 A / 31,5 V	60% 500 A / 39,0 V
	100% 180 A / 23,0 V	100% 200 A / 24,0 V	100% 270 A / 27,5 V	100% 400 A / 34,0 V
	23	23	23	23
	F (155 °C)	F (155 °C)	F (155 °C)	F (155 °C)
	F	F	F	F
	gas 36 kg	33 kg	45 kg	50 kg
	water 79 kg	107 kg	119 kg	124 kg
	625 x 340 x 540	-----	-----	-----
	910 x 340 x 995	910 x 340 x 1420	910 x 340 x 1420	910 x 340 x 1420
	gas 843.300.010	-----	-----	-----
	water 843.300.010	843.320.010	843.400.010	843.500.010



3

ProPULS 300 C | 320 | 400 | 500

