

vLinker And OBDLink C

	vLinker BM WIFI	vLinker BM BT3.0	vLinker BM BLE4.0	vLinker FD WIFI
SAE J1850-PWM	●	●	●	●
SAE J1850-VPW	●	●	●	●
ISO 9141-2	●	●	●	●
ISO 14230-4(slow)	●	●	●	●
ISO 14230-4(fast)	●	●	●	●
ISO 15765-4(CAN)	●	●	●	●
SAE J1939(CAN)	●	●	●	●
ISO 11898(raw CAN)	●	●	●	●
Single Wire CAN(GMLAN)				
Medium Speed CAN(MS-CAN)				●
Bluetooth 3.0		●	●	
Bluetooth 4.0			●	
Wi-Fi 802.11b/g	●			●
USB				
Автоотключение	●	●	●	●
Кнопка включения				
Пробуждение по OBD	●	●	●	●
Включение при подаче питания	●	●	●	●
Дистанционное включение				
Работа с Android устройствами	●	●	●	●
Работа с Apple(iOS)	●		●	●
Работа с Windows устройствами	●	●	●	●
Защита от хакеров				
Пользовательское хранилище	●	●	●	●
FEPS программирование (FORD)				
Processor	MIC3311	MIC3311	MIC3311	MIC3312
Обновление ПО	●	●	●	●
Максимальная скорость обмена данных	230 . 4k	230. 4k	230. 4k	230 . 4k
Maximum number of bytes sent	1023	1023	1023	1023

OBDLink MX+
●
●
●
●
●
●
●
●
●
●
●
●
●
●
●
●
●
●
●
●
●
STN2255
●
1M
4095