



Portable solar panel LPS 60 W LPS 100 W

Item No.	LPS 60W	Description	data
		solar panel power	single crystal silicon / 60W ±5%
		constant folding	It is composed of 4PCS 15W/18V series solar panels.
		working voltage	>18v
		working current	>3.33A
		folded size	372*274*40mm
		unfold size	1291*372*20mm
		Terminal box output parameters	1.USB1 output with A load of 5V/ 2.4a, with over current protection, short circuit protection Protection, restart under light load, voltage drop compensation 2.USB2 output QC3.0(5V/9V/12V), with overcurrent protection, short Road protection, light load restart 3.DC output 18V, overcurrent protection, short circuit protection (customizable) 4. The red LED is steady on when the output is normal, and the LED blinks when the output is abnormal

Item No.	LPS-100W	Description	data
		solar panel power	single crystal silicon /100W ±5%
		constant folding	It is composed of 4 25W/18V parallel solar panels
		working voltage	>18V
		working current	>5.55A
		folded size	506*389*60mm
		unfold size	1708*506*10mm
		Terminal box output parameters	1. USB1 output with load of 5V/ 2.4a, with over current protection, short circuit protection, voltage drop compensation, light load restart 2. USB2 output QC3.0(5V/9V/12V), with over current protection, short circuit protection, light load restart 3. Type-c output with PD45W(5V/9V/12V/15V/20V), With over current protection, short circuit protection, light load restart DC port 18V solar panel direct output (can be customized) 5 When the output is normal, the blue LED is steady on; when the output is abnormal, the red LED is steady on 6. Single USB+ Type-C +DC(switch 12V/15V)



