



**ALLIANCE  
 AGRICULTURE**

TRA: I-1  
 Speed Rating: **FI**

Alliance 543 High Speed tire is ribbed to provide excellent performance for free rolling wheels for use on harvesting machines, hay balers, bale racks, seeders, windrowers and fertilizer manure spreaders. It provides easy steering of machinery/equipment due to its heavily grooved ribs. The tire provides adequate flotation for machinery and has high density rubber compounding on its tread. This tire is DOT certified for intermittent highway use.

**IMPLEMENT - 12.5L-15FI**

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load
		SW mm	OD mm					Speed
								100 kmph
12.5L-15FI	8LBX15	318	820	366	2392	Load Range D	4.13	1696.4

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load
		SW mm	OD mm					Speed
								100 kmph
12.5L-15FI	10LBx15	318	823	375.7	2457	LOAD RANGE F	6.2	2120

For ATC Tires Pvt Limited



Dan Steltmann  
 Chief Technology Officer

