

# FARMAX R85

**FEATURE**

- Greater lug overlap

**BENEFITS**

- More lugs in footprint
- Better stability

**FEATURE**

- Larger inner volume

**BENEFITS**

- Reduced soil compaction
- Increased load carrying capacity



**FEATURES**

- Reduced space between lugs
- Mud breaker at the centre

**BENEFITS**

- Better roadability
- Increased service life
- Self cleaning

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Less soil disturbance

**FEATURE**

- Dual lug angle

**BENEFITS**

- Superior traction
- Better Roadability


**FEATURE**

- Wider tread

**BENEFITS**

- Reduced soil compaction
- Increased footprint

## MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph /mph					
				SW	OD				Static	10	20	30	40	50
				mm	mm					6	12	19	25	31
				in	in				Recommend load kg /lbs					
280/85R20	112A8/ 112B	TL	W10 W9	285 11.2	984 38.7	447 17.6	2914 114.7	0.8	1730	1130	920	800	750	750
								12	3810	2490	2030	1760	1650	1650
								1	1960	1280	1050	910	850	850
								15	4320	2820	2310	2000	1870	1870
								1.3	2280	1490	1220	1060	990	990
								19	5020	3280	2690	2330	2180	2180
								1.6	2580	1680	1380	1200	1120	1120
								23	5680	3700	3040	2640	2470	2470