

YIELDMAX



FEATURE

- R1-W Pattern

BENEFIT

- Longer tyre life

FEATURE

- Dual Lug angle

BENEFIT

- Higher traction and better stability

FEATURE

- Higher lug overlap

BENEFIT

- Enhanced road ability and load ability

FEATURE

- Strong & sharp shoulders

BENEFIT

- Better grip

FEATURE

- Wide open shoulders

BENEFIT

- Better self cleaning


FEATURE

- Rounded Lug Base

BENEFIT

- Stubble Resistance

MACHINERY



Harvester

Size	Rim	Unloaded dimension		Static Loaded	Rolling Circum	Load Index	Infl. press.	Recommend load, kg (lbs)							Cyclic operation	
		SW	OD	Radius	mm	Speed	bar	Speed, km/h (mph)								
		mm	mm	mm	mm	Symbol	psi	Constant load								
		in	in	in	in			10	20	30	40	50	10	15		
620/75R30 CHO	DW20B	620	1692	763	5103	169A8/B	0.8	5930	3870	3170	2760	2580	2580	4640	4260	
	12						13060	8520	6980	6080	5680	5680	10220	9380		
	1.6						8900	5810	4760	4140	3870	3870	6970	6390		
	23						19600	12800	10480	9120	8520	8520	15350	14070		
	2						10140	6620	5420	4720	4410	4410	7940	7280		
	29						22330	14580	11940	10400	9710	9710	17490	16040		
	2.6						11820	7710	6320	5500	5140	5140	9250	8480		
	38						26040	16980	13920	12110	11320	11320	20370	18680		
	3.2						13340	8700	7130	6210	5800	5800	10440	9570		
46	29380	19160	15700	13680	12780	12780	23000	21080								