



SAN DIEGO

Piazzetta  design

SAN DIEGO

Gas or wood-burning fireplace with handmade majolica surround.

SURROUND WEIGHT: 96 kg

GAS BURNING (NATURAL GAS OR LPG) IG 90
FIREBOX: in Aluker®

INLET: in grey enamelled steel

GLASS: ceramic heat resistant up to 750°C

FUNCTION CONTROL: remote control

CERAMIC LOGS: standard supply

HEATING: convection and radiation

FLUE GAS OUTLET: concentric pipe Ø 10/15 cm

FIREBOX HEAT OUTPUT: 9,5 kW (Natural gas)
9,5 kW (LPG)

THERMAL EFFICIENCY: 80% (Natural gas)
75% (LPG)

CONSUMPTION AT RATED HEAT OUTPUT:
0,90 m³/h (Natural gas)
720 g/h (LPG)

WEIGHT: 90 kg

RATED HEAT OUTPUT: 6,8 kW (Natural gas)
6,4 kW (LPG)

TYPE-EXAMINATION: EC certification E0780

OPTIONAL ACCESSORIES:

- river pebbles
- height regulation kit

GAS BURNING (NATURAL GAS OR LPG) IG 90 B
FIREBOX: in Aluker®

INLET: in grey enamelled steel

GLASS: ceramic heat resistant up to 750°C

FUNCTION CONTROL: remote control

CERAMIC LOGS: standard supply

HEATING: convection and radiation

FLUE GAS OUTLET: concentric pipe Ø 10/15 cm

FIREBOX HEAT OUTPUT: 9,5 kW (Natural gas)
9,5 kW (LPG)

THERMAL EFFICIENCY: 80% (Natural gas)
75% (LPG)

CONSUMPTION AT RATED HEAT OUTPUT:
0,90 m³/h (Natural gas)
720 g/h (LPG)

WEIGHT: 87 kg

RATED HEAT OUTPUT: 6,8 kW (Natural gas)
6,4 kW (LPG)

TYPE-EXAMINATION: EC certification E0780

OPTIONAL ACCESSORIES:

- river pebbles
- height regulation kit

WOOD BURNING ME 90/44

INLET: in enamelled steel

FIREBOX: in Aluker®

GRATE: in Aluker® with cast iron grid

DOOR: rise n' fall with glass ceramic heat resistant up to 750°C, may also be opened as hinged door for cleaning

PRIMARY AIR: adjustable by hand

SECONDARY AIR: pre-determined

SMOKE DAMPER: automatic and adjustable

ASH DRAWER: removable

HEATING: natural convection

or forced air circulation by

Multifuoco System® on request, with 1 or 2 ventilators.

FLUE OUTLET: Ø 25 cm

NOMINAL OUTPUT: 13,5 kW

THERMAL EFFICIENCY: 78,5 %

NOMINAL CONSUMPTION : 4 kg/h

MAX OUTPUT : 14,6 kW

MAX CONSUMPTION : 4,6 kg/h

WEIGHT: 285 kg

Laboratory measurements were made using beech wood with moisture content below 20%

Type approval in accordance with EN13229

OPTIONAL ACCESSORIES:

- ventilation kit Multifuoco System® with automatic or manual switching on and off and 4-speed remote control.
- sensor kit for dual Multifuoco System®
- adjustable height kit

WOOD BURNING ME 90/44 B

INLET: in enamelled steel

FIREBOX: in Aluker®

GRATE: in Aluker® with cast iron grid

DOOR: rise n' fall with glass ceramic heat resistant up to 750°C, may also be opened as hinged door for cleaning

PRIMARY AIR: adjustable by hand

SECONDARY AIR: pre-determined

SMOKE DAMPER: automatic and adjustable

ASH DRAWER: removable

HEATING: natural convection

or forced air circulation by

Multifuoco System® on request, with 1 ventilator.

FLUE OUTLET: Ø 25 cm

NOMINAL OUTPUT: 13,5 kW

THERMAL EFFICIENCY: 78 %

NOMINAL CONSUMPTION : 3,7 kg/h

MAX OUTPUT : 13,5 kW

MAX CONSUMPTION : 3,7 kg/h

WEIGHT: 365 kg

Laboratory measurements were made using beech wood with moisture content below 20%

Type approval in accordance with EN13229

OPTIONAL ACCESSORIES:

- ventilation kit Multifuoco System® with automatic or manual switching on and off and 4-speed remote control.
- sensor kit for dual Multifuoco System®
- adjustable height kit

DIMENSIONI:

	IG90	IG90B	ME90/44	ME90/44B
A	43	38	65	66,5
B	93	93	95	106
C	12,5	19	19,5	30
Ø	15	15	25	25

Measurements expressed in cm

