

PETROCAR 10 L/L

FUEL AND MINERAL OIL DELIVERY HOSE - LONG LENGTH



APPLICATION

Delivery hose for mineral oils, diesel fuel and gasoline with aromatic contents up to 50%

TUBE

Black, smooth, **NBR** rubber compound

REINFORCEMENT

High strength synthetic plies

COVER

Black, smooth, **NBR/PVC** rubber compound, resistant to oils, fuels, ozone and weather

WORKING TEMPERATURE

-13°F +176°F

-25°C +80°C

										
ID		OD		WEIGHT	WP		BP		BENDING RADIUS	COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	mm	m
4	5/32	10	3/8	0.10	10	150	30	450	40	100
5	3/16	12	15/32	0.12	10	150	30	450	40	100
6	1/4	13	1/2	0.13	10	150	30	450	50	100
7	9/32	14	35/64	0.14	10	150	30	450	60	100
8	5/16	15	19/32	0.17	10	150	30	450	65	100
10	3/8	17	43/64	0.20	10	150	30	450	80	100
13	1/2	20	25/32	0.24	10	150	30	450	105	50
15	19/32	23	29/32	0.32	10	150	30	450	120	50
19	3/4	27	1 5/8	0.39	10	150	30	450	150	50
25	1	35	1 3/8	0.63	10	150	30	450	200	50

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

TGT PETROCAR W.P. 10 BAR ITALY