


Product Datasheet model ultrasonic CR 9302 500

**UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,
D-90766 Fürth**

**Autoclavable
safety eyewear
that makes the
difference**

- Professional protection of products and humans for medical and pharmaceutical industries
- First autoclavable protective overspec with anti-fog effect
- Sterile eye protection in every situation
- Autoclavable 20 times, 121°C, 20 min.
- Innovative design for maximum functionality and wearer comfort
- Ultra-light goggle with panorama lens, duo component technology and adjustable silicone headband
- Indirect ventilation ensures a pleasant and comfortable interior environment
- Easy lens replacement
- Flexible soft components
- Wide panoramic field of vision
- Non-allergenic material which is free of harmful substances

<p>Product characteristics</p>	<ul style="list-style-type: none"> • Ultra-light goggle with panorama lens • Antifog coating inside • Indirect ventilation • Adjustable silicone headband • Suitable for use over prescription spectacles • Suitable for cleanroom environments • Optical class 1 • Particularly suitable for combination with other PPE (e.g. face masks) • UV 400 protection
<p>Sterilisation</p>	<p>Suitable for autoclave sterilization. 20 cycles, at 121°C for 20 minutes each.</p>
<p>Disinfection</p>	<p>Commercially available disinfectants (Isopropanol) can be used, either by spraying or wiping. Goggles should not be placed in disinfectant for an extended period of time. It is also possible to make a machine clean the goggle in the pre-wash process.</p>
<p>Technical details</p>	
<p>Frame</p>	
<p>Material</p>	<p>PP/TPE</p>
<p>Colour</p>	<p>transparent/white</p>
<p>Manufacturer's ID code</p>	<p>Marking W</p>
<p>EN norm</p>	<p>166</p>
<p>Field of use</p>	<p>3 (drops and splashes of liquid) 4 (large dust particles)</p>
<p>Impact resistance</p>	<p>B (120 m/s)</p>
<p>Conformity symb.</p>	<p>CE</p>

Material	Headband
Features	silicone
Colour	continuously adjustable
	white, transparent
Lens	
Material	PC
Thickness	2.2 mm
Coating	uvex supravision clean
Colour	clear
UV protection	UV 400
	Marking
Filter	2-1,2 (DIN EN 170)
Manufacturer's ID code	W
Optical class	1
Impact resistance	B (120 m/s)
Surface resistance to fine particles	K
Antifog	N
Conformity symb.	CE
Factory symbol	
Miscellaneous	
Weight	98 g
Packing	4 goggles per box
	72 goggles per cardboard box
Standards	DIN EN 166 + 170
PPE Category	Category II