

Power generator

F 4001 i

Nr art. 35944

Engine

Noise level Lwa



Characteristic

- Stable frequency 50 Hz
- Inverter technology
- Voltage stabilization ± 1 %
- Low level of THD ≤ 3 %
- Weight only 26kg

- Fuel saving function reduce engine speed at low load
- Possibility of synchronization two units F 4001 I

Technical parameters

Frequency 50 Hz
Voltage 230 V
Maximum power 3,2 kW
Nominal power 3,0 kW
Prime current 13,0 A

Model SH 150 B 149 cm³ Capacity Cooling Air Cylinder 1 Stroke 4 Oil volume 0,5 L Manual Starting system Petrol Fuel Fuel tank 10,0 L Consumption (load 50/100%) 0,91/1,67L/h

Senci

96 dB(A)

Weight 26 kg
Lenght 479 mm
Width 340 mm
Hight 442 mm

Standard equipment

- Display V, Hz, h
- 2 Sockets 230 V 16 A
- USB Socket
- Socket and cables for battery charging 12 V 8,3 A
- Overload sygnalization
- Overload protection
- Low oil warning diode
- Synchronization cables for two generators F4001 IS

Optional and service equipment

Service kit

(air filter, spark plug, engine oil)

Nr art. 36603

Norms and Directives

- 2000/14/WE

Noise Directive 2005/88/WE

- 2006/42/WE

Machinery Directive

- 2014/35/UE

Low Voltage Directive

• 2014/30/UE

EC Directive