


**Product Datasheet model ultravision 9301 116**

**UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,  
D-90766 Fürth**

**Product  
characteristics**

- Anatomical shape and soft material allow close, yet comfortable fit
- Additional comfort cushioning
- Fits comfortably over most prescription spectacles
- Nose bridge works well with respirators
- Frosted top to reduce glare
- High-quality, easily adjustable headband
- Optically correct lens (EN 166 class 1) does not distort view or cause headaches
- Eye protection suitable for oil and gas applications

<b>Technical details</b>	
<b>Frame</b>	<b>Front piece</b>
Material	PVC
Features	ventilation system / face foam velour
Colour	transparent light grey
	<b>Headband</b>
Material	synthetic headband
Features	adjustable
Colour	black/grey
	<b>Marking</b>
Manufacturer's ID code	W
Applicable EN norm	166
Field of use	3 (drops and splashes of liquid) 4 (large dust particles)
Impact resistance	B (120 m/s)
Conformity symbol	CE
<b>Lens</b>	
Material	PC
Thickness	1,2 mm
Coating	uvex supravision plus
Colour	clear
UV protection	UV 400

	<b>Marking</b>
Filter	2C-1,2 (DIN EN 170)
Manufacturer's ID code	W
Optical class	1
Impact resistance	B (120 m/s)
Field of use	9 (molten material and hot solids)
Surface resistance to fine particles	K
Antifog	N
Conformity symbol	CE
Factory symbol	
 <b>Miscellaneous</b>	
Weight	121 g
Packing	80 pieces in one carton
Standards	DIN EN 166 + DIN EN 170
PPE Category	Category II