



**BORMA WACHS**<sup>®</sup>

Wood Professional Cosmetics

## Technical data Sheet

REV 00 of 20.10.2012

# HARTWACHS OIL 7030

## Hard Wax Oil

### DESCRIPTION:

HARTWACHS OIL 7030 is a natural wax dispersion in valuable oils, repolishable, for the treatment and finishing of every raw wood surface. Considerably hard, it has an excellent resistance to water.

Extremely easy to apply, it is perfect for the ordinary and extraordinary maintenance of the oil treated surfaces.

### CHEMICAL/PHYSICAL CHARACTERISTICS:

<b>Composition:</b>	Hard wax dispersion in oil
<b>Odour:</b>	Characteristic
<b>Form:</b>	Creamy fluid
<b>Solubility:</b>	Soluble in solvent
<b>Dilution:</b>	Solvoil line
<b>Yield:</b>	10/12 m <sup>2</sup> /L

### METHOD OF USE:

Ready to use. Spread HARTWACHS OIL 7030 uniformly, using a brush or a cloth, on a clean surface, free from dust, grease and oils. Once dried (after 6/8 h, depending on the thickness and on the temperature), sand with 220/240 grain to obtain an increased softness. Then proceed with the application of a second coating and, once dried, to obtain a soft and smooth satin sheen, polish with the brushes of the Borma range or buff vigorously with a soft cotton cloth. Complete drying after 12 h. Maximum hardness after 24 h.

### STORAGE:

Store in a cool, well ventilated place, keep the container closed when not in use. Keep away from heat, flames, sparks and other sources of ignition.

### PACKAGING:

The product comes in 750 mL, Lt 5 and Lt 15 sized cans.

### WARNING:

Sawdust, cotton cloth, paper and similar products soaked with liquid product and let in such condition may cause spontaneous combustion. Therefore, in case of presence of these materials for cleaning, ensure adequate air ventilation of the rooms in order to allow a rapid drying of the product or wet them with water before disposal.